

## HS 50 M

## HS 50M



Spring heads will separate

### TECHNICAL SPECIFICATIONS

Max hose size 2" (internal & external)  
 Control Manual  
 Weight (kg) 2,35  
 Dimensions (LxWxH max) 453 x 205 x 58

SERIES RANGE	
External size	Range (mm)
3/8"	0-55
1/2"	0-55
3/4"	0-55
1"	0-55
1 1/4"	0-55
1 1/2"	0-55
2"	0-55 / 15-58
2 1/2"	0-55 / 15-58
3"	0-55 / 15-58
3 1/2"	0-55 / 15-58
4"	0-55 / 15-58
4 1/2"	0-55 / 15-58
5"	0-55 / 15-58
5 1/2"	0-55 / 15-58
6"	0-55 / 15-58
6 1/2"	0-55 / 15-58
7"	0-55 / 15-58
7 1/2"	0-55 / 15-58
8"	0-55 / 15-58
8 1/2"	0-55 / 15-58
9"	0-55 / 15-58
9 1/2"	0-55 / 15-58
10"	0-55 / 15-58
10 1/2"	0-55 / 15-58
11"	0-55 / 15-58
11 1/2"	0-55 / 15-58
12"	0-55 / 15-58
12 1/2"	0-55 / 15-58
13"	0-55 / 15-58
13 1/2"	0-55 / 15-58
14"	0-55 / 15-58
14 1/2"	0-55 / 15-58
15"	0-55 / 15-58
15 1/2"	0-55 / 15-58
16"	0-55 / 15-58
16 1/2"	0-55 / 15-58
17"	0-55 / 15-58
17 1/2"	0-55 / 15-58
18"	0-55 / 15-58
18 1/2"	0-55 / 15-58
19"	0-55 / 15-58
19 1/2"	0-55 / 15-58
20"	0-55 / 15-58
20 1/2"	0-55 / 15-58
21"	0-55 / 15-58
21 1/2"	0-55 / 15-58
22"	0-55 / 15-58
22 1/2"	0-55 / 15-58
23"	0-55 / 15-58
23 1/2"	0-55 / 15-58
24"	0-55 / 15-58
24 1/2"	0-55 / 15-58
25"	0-55 / 15-58
25 1/2"	0-55 / 15-58
26"	0-55 / 15-58
26 1/2"	0-55 / 15-58
27"	0-55 / 15-58
27 1/2"	0-55 / 15-58
28"	0-55 / 15-58
28 1/2"	0-55 / 15-58
29"	0-55 / 15-58
29 1/2"	0-55 / 15-58
30"	0-55 / 15-58
30 1/2"	0-55 / 15-58
31"	0-55 / 15-58
31 1/2"	0-55 / 15-58
32"	0-55 / 15-58
32 1/2"	0-55 / 15-58
33"	0-55 / 15-58
33 1/2"	0-55 / 15-58
34"	0-55 / 15-58
34 1/2"	0-55 / 15-58
35"	0-55 / 15-58
35 1/2"	0-55 / 15-58
36"	0-55 / 15-58
36 1/2"	0-55 / 15-58
37"	0-55 / 15-58
37 1/2"	0-55 / 15-58
38"	0-55 / 15-58
38 1/2"	0-55 / 15-58
39"	0-55 / 15-58
39 1/2"	0-55 / 15-58
40"	0-55 / 15-58
40 1/2"	0-55 / 15-58
41"	0-55 / 15-58
41 1/2"	0-55 / 15-58
42"	0-55 / 15-58
42 1/2"	0-55 / 15-58
43"	0-55 / 15-58
43 1/2"	0-55 / 15-58
44"	0-55 / 15-58
44 1/2"	0-55 / 15-58
45"	0-55 / 15-58
45 1/2"	0-55 / 15-58
46"	0-55 / 15-58
46 1/2"	0-55 / 15-58
47"	0-55 / 15-58
47 1/2"	0-55 / 15-58
48"	0-55 / 15-58
48 1/2"	0-55 / 15-58
49"	0-55 / 15-58
49 1/2"	0-55 / 15-58
50"	0-55 / 15-58
50 1/2"	0-55 / 15-58
51"	0-55 / 15-58
51 1/2"	0-55 / 15-58
52"	0-55 / 15-58
52 1/2"	0-55 / 15-58
53"	0-55 / 15-58
53 1/2"	0-55 / 15-58
54"	0-55 / 15-58
54 1/2"	0-55 / 15-58
55"	0-55 / 15-58
55 1/2"	0-55 / 15-58
56"	0-55 / 15-58
56 1/2"	0-55 / 15-58
57"	0-55 / 15-58
57 1/2"	0-55 / 15-58
58"	0-55 / 15-58
58 1/2"	0-55 / 15-58
59"	0-55 / 15-58
59 1/2"	0-55 / 15-58
60"	0-55 / 15-58
60 1/2"	0-55 / 15-58
61"	0-55 / 15-58
61 1/2"	0-55 / 15-58
62"	0-55 / 15-58
62 1/2"	0-55 / 15-58
63"	0-55 / 15-58
63 1/2"	0-55 / 15-58
64"	0-55 / 15-58
64 1/2"	0-55 / 15-58
65"	0-55 / 15-58
65 1/2"	0-55 / 15-58
66"	0-55 / 15-58
66 1/2"	0-55 / 15-58
67"	0-55 / 15-58
67 1/2"	0-55 / 15-58
68"	0-55 / 15-58
68 1/2"	0-55 / 15-58
69"	0-55 / 15-58
69 1/2"	0-55 / 15-58
70"	0-55 / 15-58
70 1/2"	0-55 / 15-58
71"	0-55 / 15-58
71 1/2"	0-55 / 15-58
72"	0-55 / 15-58
72 1/2"	0-55 / 15-58
73"	0-55 / 15-58
73 1/2"	0-55 / 15-58
74"	0-55 / 15-58
74 1/2"	0-55 / 15-58
75"	0-55 / 15-58
75 1/2"	0-55 / 15-58
76"	0-55 / 15-58
76 1/2"	0-55 / 15-58
77"	0-55 / 15-58
77 1/2"	0-55 / 15-58
78"	0-55 / 15-58
78 1/2"	0-55 / 15-58
79"	0-55 / 15-58
79 1/2"	0-55 / 15-58
80"	0-55 / 15-58
80 1/2"	0-55 / 15-58
81"	0-55 / 15-58
81 1/2"	0-55 / 15-58
82"	0-55 / 15-58
82 1/2"	0-55 / 15-58
83"	0-55 / 15-58
83 1/2"	0-55 / 15-58
84"	0-55 / 15-58
84 1/2"	0-55 / 15-58
85"	0-55 / 15-58
85 1/2"	0-55 / 15-58
86"	0-55 / 15-58
86 1/2"	0-55 / 15-58
87"	0-55 / 15-58
87 1/2"	0-55 / 15-58
88"	0-55 / 15-58
88 1/2"	0-55 / 15-58
89"	0-55 / 15-58
89 1/2"	0-55 / 15-58
90"	0-55 / 15-58
90 1/2"	0-55 / 15-58
91"	0-55 / 15-58
91 1/2"	0-55 / 15-58
92"	0-55 / 15-58
92 1/2"	0-55 / 15-58
93"	0-55 / 15-58
93 1/2"	0-55 / 15-58
94"	0-55 / 15-58
94 1/2"	0-55 / 15-58
95"	0-55 / 15-58
95 1/2"	0-55 / 15-58
96"	0-55 / 15-58
96 1/2"	0-55 / 15-58
97"	0-55 / 15-58
97 1/2"	0-55 / 15-58
98"	0-55 / 15-58
98 1/2"	0-55 / 15-58
99"	0-55 / 15-58
99 1/2"	0-55 / 15-58
100"	0-55 / 15-58
100 1/2"	0-55 / 15-58

Name

HS 50M