

## HS 50 M

## HS 50M



Spring heads will separate

### TECHNICAL SPECIFICATIONS

Max hose size 2" (internal & external)  
 Control Manual  
 Weight (kg) 2,35  
 Dimensions (LxWxH max) 453 x 205 x 58

SERIES RANGE	
External size	Range (mm)
3/8"	0-55
1/2"	0-55
5/8"	0-55
3/4"	0-55
1 1/4"	0-55
1 1/2"	0-55
2"	0-55 / 15-98
2 1/2"	0-55 / 15-98
3"	0-55 / 15-98
3 1/2"	0-55 / 15-98
4"	0-55 / 15-98
4 1/2"	0-55 / 15-98
5"	0-55 / 15-98
5 1/2"	0-55 / 15-98
6"	0-55 / 15-98
6 1/2"	0-55 / 15-98
7"	0-55 / 15-98
7 1/2"	0-55 / 15-98
8"	0-55 / 15-98
8 1/2"	0-55 / 15-98
9"	0-55 / 15-98
9 1/2"	0-55 / 15-98
10"	0-55 / 15-98
10 1/2"	0-55 / 15-98
11"	0-55 / 15-98
11 1/2"	0-55 / 15-98
12"	0-55 / 15-98
12 1/2"	0-55 / 15-98
13"	0-55 / 15-98
13 1/2"	0-55 / 15-98
14"	0-55 / 15-98
14 1/2"	0-55 / 15-98
15"	0-55 / 15-98
15 1/2"	0-55 / 15-98
16"	0-55 / 15-98
16 1/2"	0-55 / 15-98
17"	0-55 / 15-98
17 1/2"	0-55 / 15-98
18"	0-55 / 15-98
18 1/2"	0-55 / 15-98
19"	0-55 / 15-98
19 1/2"	0-55 / 15-98
20"	0-55 / 15-98
20 1/2"	0-55 / 15-98
21"	0-55 / 15-98
21 1/2"	0-55 / 15-98
22"	0-55 / 15-98
22 1/2"	0-55 / 15-98
23"	0-55 / 15-98
23 1/2"	0-55 / 15-98
24"	0-55 / 15-98
24 1/2"	0-55 / 15-98
25"	0-55 / 15-98
25 1/2"	0-55 / 15-98
26"	0-55 / 15-98
26 1/2"	0-55 / 15-98
27"	0-55 / 15-98
27 1/2"	0-55 / 15-98
28"	0-55 / 15-98
28 1/2"	0-55 / 15-98
29"	0-55 / 15-98
29 1/2"	0-55 / 15-98
30"	0-55 / 15-98
30 1/2"	0-55 / 15-98
31"	0-55 / 15-98
31 1/2"	0-55 / 15-98
32"	0-55 / 15-98
32 1/2"	0-55 / 15-98
33"	0-55 / 15-98
33 1/2"	0-55 / 15-98
34"	0-55 / 15-98
34 1/2"	0-55 / 15-98
35"	0-55 / 15-98
35 1/2"	0-55 / 15-98
36"	0-55 / 15-98
36 1/2"	0-55 / 15-98
37"	0-55 / 15-98
37 1/2"	0-55 / 15-98
38"	0-55 / 15-98
38 1/2"	0-55 / 15-98
39"	0-55 / 15-98
39 1/2"	0-55 / 15-98
40"	0-55 / 15-98
40 1/2"	0-55 / 15-98
41"	0-55 / 15-98
41 1/2"	0-55 / 15-98
42"	0-55 / 15-98
42 1/2"	0-55 / 15-98
43"	0-55 / 15-98
43 1/2"	0-55 / 15-98
44"	0-55 / 15-98
44 1/2"	0-55 / 15-98
45"	0-55 / 15-98
45 1/2"	0-55 / 15-98
46"	0-55 / 15-98
46 1/2"	0-55 / 15-98
47"	0-55 / 15-98
47 1/2"	0-55 / 15-98
48"	0-55 / 15-98
48 1/2"	0-55 / 15-98
49"	0-55 / 15-98
49 1/2"	0-55 / 15-98
50"	0-55 / 15-98
50 1/2"	0-55 / 15-98
51"	0-55 / 15-98
51 1/2"	0-55 / 15-98
52"	0-55 / 15-98
52 1/2"	0-55 / 15-98
53"	0-55 / 15-98
53 1/2"	0-55 / 15-98
54"	0-55 / 15-98
54 1/2"	0-55 / 15-98
55"	0-55 / 15-98
55 1/2"	0-55 / 15-98
56"	0-55 / 15-98
56 1/2"	0-55 / 15-98
57"	0-55 / 15-98
57 1/2"	0-55 / 15-98
58"	0-55 / 15-98
58 1/2"	0-55 / 15-98
59"	0-55 / 15-98
59 1/2"	0-55 / 15-98
60"	0-55 / 15-98
60 1/2"	0-55 / 15-98
61"	0-55 / 15-98
61 1/2"	0-55 / 15-98
62"	0-55 / 15-98
62 1/2"	0-55 / 15-98
63"	0-55 / 15-98
63 1/2"	0-55 / 15-98
64"	0-55 / 15-98
64 1/2"	0-55 / 15-98
65"	0-55 / 15-98
65 1/2"	0-55 / 15-98
66"	0-55 / 15-98
66 1/2"	0-55 / 15-98
67"	0-55 / 15-98
67 1/2"	0-55 / 15-98
68"	0-55 / 15-98
68 1/2"	0-55 / 15-98
69"	0-55 / 15-98
69 1/2"	0-55 / 15-98
70"	0-55 / 15-98
70 1/2"	0-55 / 15-98
71"	0-55 / 15-98
71 1/2"	0-55 / 15-98
72"	0-55 / 15-98
72 1/2"	0-55 / 15-98
73"	0-55 / 15-98
73 1/2"	0-55 / 15-98
74"	0-55 / 15-98
74 1/2"	0-55 / 15-98
75"	0-55 / 15-98
75 1/2"	0-55 / 15-98
76"	0-55 / 15-98
76 1/2"	0-55 / 15-98
77"	0-55 / 15-98
77 1/2"	0-55 / 15-98
78"	0-55 / 15-98
78 1/2"	0-55 / 15-98
79"	0-55 / 15-98
79 1/2"	0-55 / 15-98
80"	0-55 / 15-98
80 1/2"	0-55 / 15-98
81"	0-55 / 15-98
81 1/2"	0-55 / 15-98
82"	0-55 / 15-98
82 1/2"	0-55 / 15-98
83"	0-55 / 15-98
83 1/2"	0-55 / 15-98
84"	0-55 / 15-98
84 1/2"	0-55 / 15-98
85"	0-55 / 15-98
85 1/2"	0-55 / 15-98
86"	0-55 / 15-98
86 1/2"	0-55 / 15-98
87"	0-55 / 15-98
87 1/2"	0-55 / 15-98
88"	0-55 / 15-98
88 1/2"	0-55 / 15-98
89"	0-55 / 15-98
89 1/2"	0-55 / 15-98
90"	0-55 / 15-98
90 1/2"	0-55 / 15-98
91"	0-55 / 15-98
91 1/2"	0-55 / 15-98
92"	0-55 / 15-98
92 1/2"	0-55 / 15-98
93"	0-55 / 15-98
93 1/2"	0-55 / 15-98
94"	0-55 / 15-98
94 1/2"	0-55 / 15-98
95"	0-55 / 15-98
95 1/2"	0-55 / 15-98
96"	0-55 / 15-98
96 1/2"	0-55 / 15-98
97"	0-55 / 15-98
97 1/2"	0-55 / 15-98
98"	0-55 / 15-98
98 1/2"	0-55 / 15-98
99"	0-55 / 15-98
99 1/2"	0-55 / 15-98
100"	0-55 / 15-98
100 1/2"	0-55 / 15-98

Name

HS 50M