



AOL / AOS - fitting pressed, DKOL / DKOS

Scope
 Connection 1
 Seal type 1
 Standard

Standard code
 Stuff
 Surface protection

Measuring devices and accessories
 Metric inner thread
 24 ° outer cone with O-ring
 DIN 3865
 ISO 8434-4
 DIN ISO 12151-2
 DKOL
 steel
 Galvanized

| Name | DN | Size | Cal | G1 | L1 (mm) | S1 | Typoszereg do średnicy OR zew. rury Ø mm | | |
|-----------------|----|------|-------|------------|---------|----|--|----|-----------|
| PN 02 AOL 04 | 2 | 1 | 5/64" | M 12 x 1,5 | 35,0 | 14 | L | 6 | 4,0 x 1,5 |
| PN 02 AOL 06 | 2 | 1 | 5/64" | M 14 x 1,5 | 34,0 | 17 | L | 8 | 6,0 x 1,5 |
| PN 02 AOL 08 | 2 | 1 | 5/64" | M 16 x 1,5 | 36,5 | 19 | L | 10 | 7,5 x 1,5 |
| PN 02 AOL 10 | 2 | 1 | 5/64" | M 18 x 1,5 | 37,5 | 22 | L | 12 | 9,0 x 1,5 |
| PN 02 AOS 03 | 2 | 1 | 5/64" | M 14 x 1,5 | 35,0 | 17 | S | 6 | 4,0 x 1,5 |
| PN 02 AOS 04 | 2 | 1 | 5/64" | M 16 x 1,5 | 35,0 | 19 | S | 8 | 6,0 x 1,5 |
| PN 02 AOS 06 | 2 | 1 | 5/64" | M 18 x 1,5 | 36,5 | 22 | S | 10 | 7,5 x 1,5 |
| PN 02 AOS 08 | 2 | 1 | 5/64" | M 20 x 1,5 | 37,5 | 24 | S | 12 | 9,0 x 1,5 |