



## HS - ending simple metric tough - external thread

Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1  
Sealing form 1

metric cylindrical outer thread  
24° inner cone

Short code

CES

Standard

ISO 8434-1

Series

heavy

Material

Steel

Surface

electro galvanised

Name	DN	Size	Screw	φ
PN 04 HS	4	3	M 16x1,5	8
PN 06 HS 03	6	4	M 14x1,5	6
PN 06 HS 04	6	4	M 16x1,5	8
PN 06 HS	6	4	M 18x1,5	10
PN 06 HS 08	6	4	M 20x1,5	12
PN 08 HS	8	5	M 20x1,5	12
PN 08 HS 06	8	5	M 18x1,5	10
PN 10 HS 08	10	8	M 20x1,5	12
PN 10 HS	10	6	M 22x1,5	14
PN 13 HS 16	13	8	M 30x2	20
PN 16 HS 13	16	10	M 24x1,5	16
PN 16 HS	16	10	M 30x2	20
PN 20 HS 16	20	12	M 30x2	20
PN 20 HS	20	12	M 36x2	25
PN 25 HS 20	25	16	M 36x2	25
PN 25 HS	25	16	M 42x2	30
PN 32 HS 25	32	20	M 42x2	30
PN 32 HS	32	20	M 52x2	38
PN 13 HS	13	8	M 24x1,5	16