



HFM KL 12 / HFM KS 12 - Measuring connection, S12.65 x 1.5 series

Connection 1
Sealing form 1
Connection 2
Design

Series
Standard
Included in scope of supply
Temp. min.
Temp. max.
Material
Surface

metric nut thread
24° outer cone with O-ring
Measuring connection S 12.65 x 1.5
Measuring connection with 24° sealing head (DKO)
light and heavy
ISO 8434-1
with cap
-25 °C
100 °C
Steel
electro galvanised

Name	Ciśn. rob. (bar)	G1	Typoszereg	OR	Średnica zew. rury Ø (mm)
HFM KL 10-12	315	M 16 x 1,5	L	7,5 x 1,5	10
HFM KL 06-12	315	M 12 x 1,5	L	4,0 x 1,5	6
HFM KL 08-12	315	M 14 x 1,5	L	6,0 x 1,5	8
HFM KL 18-12	315	M 26 x 1,5	L	15,0 x 2,0	18
HFM KL 12-12	315	M 18 x 1,5	L	9,0 x 1,5	12
HFM KL 15-12	315	M 22 x 1,5	L	12,0 x 2,0	15
HFM KL 35-12	160	M 45 x 2	L	32,0 x 2,5	35
HFM KL 22-12	160	M 30 x 2	L	16,3 x 2,4	22
HFM KS 06-12	630	M 14 x 1,5	S	6,0 x 1,5	6
HFM KS 08-12	630	M 16 x 2	S	7,5 x 1,5	8
HFM KS 10-12	630	M 18 x 1,5	S	9,0 x 1,5	10
HFM KS 12-12	630	M 20 x 1,5	S	9,0 x 1,5	12
HFM KS 14-12	630	M 22 x 1,5	S	12,0 x 2,0	14
HFM KS 16-12	400	M 24 x 1,5	S	12,0 x 2,0	16
HFM KS 20-12	400	M 30 x 2	S	16,3 x 2,4	20
HFM KS 30-12	400	M 42 x 2	S	25,3 x 2,4	30
HFM KS 38-12	315	M 52 x 2	S	38,0 x 2,5	38