



## HFM T HL 12 / HFM T HS 12 - Measuring connection, S12.65 x 1.5 series

**Connection 1 + 2**  
**Sealing form 1 + 2**  
**Connection 3**  
**Construction**  
**Standard**

**Included in scope of supply**

**Temp. min.**

**Temp. max.**

**Material**

**Surface**

metric cylindrical outer thread  
 24° inner cone  
 Measuring connection S 12.65 x 1.5  
 T shaped  
 DIN 2353  
 ISO 8434-1  
 with cap  
 -25 °C  
 100 °C  
 Steel  
 electro galvanised

| Name           | Ciśn. rob. (bar) | Typozereg | Średnica zew. rury Ø (mm) | G1 + G2    |
|----------------|------------------|-----------|---------------------------|------------|
| HFM T HL 04-12 | 315              | L         | 6                         | M 12 x 1,5 |
| HFM T HL 06-12 | 315              | L         | 8                         | M 14 x 1,5 |
| HFM T HL 08-12 | 315              | L         | 10                        | M 16 x 1,5 |
| HFM T HL 10-12 | 315              | L         | 12                        | M 18 x 1,5 |
| HFM T HL 13-12 | 315              | L         | 15                        | M 22 x 1,5 |
| HFM T HL 16-12 | 315              | L         | 18                        | M 26 x 1,5 |
| HFM T HL 20-12 | 160              | L         | 22                        | M 30 x 2   |
| HFM T HL 25-12 | 160              | L         | 28                        | M 36 x 2   |
| HFM T HL 32-12 | 160              | L         | 35                        | M 45 x 2   |
| HFM T HL 40-12 | 160              | L         | 42                        | M 52 x 2   |
| HFM T HS 03-12 | 630              | S         | 6                         | M 14 x 1,5 |
| HFM T HS 04-12 | 630              | S         | 8                         | M 16 x 1,5 |
| HFM T HS 06-12 | 630              | S         | 10                        | M 18 x 1,5 |
| HFM T HS 08-12 | 630              | S         | 12                        | M 20 x 1,5 |
| HFM T HS 10-12 | 630              | S         | 14                        | M 22 x 1,5 |
| HFM T HS 13-12 | 400              | S         | 16                        | M 24 x 1,5 |
| HFM T HS 16-12 | 400              | S         | 20                        | M 30 x 2   |
| HFM T HS 20-12 | 400              | S         | 25                        | M 36 x 2   |
| HFM T HS 25-12 | 400              | S         | 30                        | M 42 x 2   |
| HFM T HS 32-12 | 315              | S         | 38                        | M 52 x 2   |