



## HFM T HL 12 / HFM T HS 12 - Measuring connection, S12.65 x 1.5 series

**Connection 1 + 2**  
**Sealing form 1 + 2**  
**Connection 3**  
**Construction**  
**Standard**

**Included in scope of supply**

**Temp. min.**

**Temp. max.**

**Material**

**Surface**

metric cylindrical outer thread  
 24° inner cone  
 Measuring connection S 12.65 x 1.5  
 T shaped  
 DIN 2353  
 ISO 8434-1  
 with cap  
 -25 °C  
 100 °C  
 Steel  
 electro galvanised

Name	Ciśn. rob. (bar)	Typozereg	Średnica zew. rury Ø (mm)	G1 + G2
HFM T HL 04-12	315	L	6	M 12 x 1,5
HFM T HL 06-12	315	L	8	M 14 x 1,5
HFM T HL 08-12	315	L	10	M 16 x 1,5
HFM T HL 10-12	315	L	12	M 18 x 1,5
HFM T HL 13-12	315	L	15	M 22 x 1,5
HFM T HL 16-12	315	L	18	M 26 x 1,5
HFM T HL 20-12	160	L	22	M 30 x 2
HFM T HL 25-12	160	L	28	M 36 x 2
HFM T HL 32-12	160	L	35	M 45 x 2
HFM T HL 40-12	160	L	42	M 52 x 2
HFM T HS 03-12	630	S	6	M 14 x 1,5
HFM T HS 04-12	630	S	8	M 16 x 1,5
HFM T HS 06-12	630	S	10	M 18 x 1,5
HFM T HS 08-12	630	S	12	M 20 x 1,5
HFM T HS 10-12	630	S	14	M 22 x 1,5
HFM T HS 13-12	400	S	16	M 24 x 1,5
HFM T HS 16-12	400	S	20	M 30 x 2
HFM T HS 20-12	400	S	25	M 36 x 2
HFM T HS 25-12	400	S	30	M 42 x 2
HFM T HS 32-12	315	S	38	M 52 x 2