



HFM KL / HFM KS - Measuring connection, M16 x 2 series

Connection 1
Sealing form 1
Connection 2
Design

Standard Series
Included in scope of supply
Temp. min.
Temp. max.
Material
Surface

metric nut thread
24° outer cone with O-ring
Measuring connection M 16 x 2
Measuring connection with 24° sealing head (DKO)
ISO 8434-1
light and heavy
with cap
-20 °C
100 °C
Steel
electro galvanised

| Name | Ciśn. rob. (bar) | G1 | Typoszereg | OR | Średnica zew. rury Ø (mm) |
|-----------|------------------|------------|------------|------------|---------------------------|
| HFM KL 06 | 315 | M 12 x 1,5 | L | 4,0 x 1,5 | 6 |
| HFM KL 08 | 315 | M 14 x 1,5 | L | 6,0 x 1,5 | 8 |
| HFM KL 10 | 315 | M 16 x 1,5 | L | 7,5 x 1,5 | 10 |
| HFM KL 12 | 315 | M 18 x 1,5 | L | 9,0 x 1,5 | 12 |
| HFM KL 15 | 315 | M 22 x 1,5 | L | 12,0 x 2,0 | 15 |
| HFM KL 18 | 315 | M 26 x 1,5 | L | 15,0 x 2,0 | 18 |
| HFM KL 22 | 160 | M 30 x 2 | L | 16,3 x 2,4 | 22 |
| HFM KL 28 | 160 | M 36 x 2 | L | 26,0 x 2,0 | 28 |
| HFM KL 35 | 160 | M 45 x 2 | L | 32,0 x 2,5 | 35 |
| HFM KL 42 | 160 | M 52 x 2 | L | 38,0 x 2,5 | 42 |
| HFM KS 06 | 630 | M 14 x 1,5 | S | 6,0 x 1,5 | 6 |
| HFM KS 08 | 630 | M 16 x 1,5 | S | 7,5 x 1,5 | 8 |
| HFM KS 10 | 630 | M 18 x 1,5 | S | 9,0 x 1,5 | 10 |
| HFM KS 12 | 630 | M 20 x 1,5 | S | 9,0 x 1,5 | 12 |
| HFM KS 14 | 630 | M 22 x 1,5 | S | 12,0 x 2,0 | 14 |
| HFM KS 16 | 400 | M 24 x 1,5 | S | 12,0 x 2,0 | 16 |
| HFM KS 20 | 400 | M 30 x 2 | S | 16,3 x 2,4 | 20 |
| HFM KS 25 | 400 | M 36 x 2 | S | 26,0 x 2,0 | 25 |
| HFM KS 30 | 400 | M 42 x 2 | S | 25,3 x 2,4 | 30 |
| HFM KS 38 | 315 | M 52 x 2 | S | 38,0 x 2,5 | 38 |