



## AB - tip straight BSP

Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1  
 Sealing form 1  
 Short code  
 Standard

BSP nut thread  
 60° outer cone  
 DKR  
 ISO 8434-6  
 BS 5200

Material  
 Surface

Steel  
 electro galvanised

Name	DN	Size	Screw
PN 04 AB	4	3	1/8"
PN 04 AB 06	4	3	1/4"
PN 06 AB 02	6	4	1/8"
PN 06 AB	6	4	1/4"
PN 06 AB 10	6	4	3/8"
PN 08 AB 06	8	5	1/4"
PN 08 AB 10	8	5	3/8"
PN 08 AB 13	8	5	1/2"
PN 10 AB 06	10	6	1/4"
PN 10 AB	10	6	3/8"
PN 10 AB 13	10	6	1/2"
PN 13 AB 10	13	8	3/8"
PN 13 AB	13	8	1/2"
PN 13 AB 16	13	8	5/8"
PN 13 AB 20	13	8	3/4"
PN 16 AB 13	16	10	1/2"
PN 16 AB	16	10	5/8"
PN 16 AB 20	16	10	3/4"
PN 16 AB 25	16	10	1"
PN 20 AB 13	20	12	1/2"
PN 20 AB 16	20	12	5/8"
PN 20 AB	20	12	3/4"
PN 20 AB 25	20	12	1"
PN 25 AB	25	16	1"
PN 25 AB 32	25	16	1 1/4"
PN 32 AB	32	20	1 1/4"
PN 32 AB 40	32	20	1 1/2"
PN 40 AB	40	24	1 1/2"

<b>Name</b>	<b>DN</b>	<b>Size</b>	<b>Screw</b>
PN 40 AB 50	40	24	2"
PN 50 AB	50	32	2"