



## HFM T HL HS - measuring connection, M 16x2

Connection 1 + 2	metric cylindrical outer thread
Seal type 1 + 2	24 ° inner cone
Connection 3	Measuring connection M 16 x 2
Type of construction	Measuring connection with 24 ° inner cone
Form	tee
Series	light and heavy
Standard	DIN 2353
Delivery range	with closing cap
Temperature min.	-20 ° C
Temperature max.	100 ° C
Stuff	steel
Surface protection	Galvanized

Name	Ciśn. rob. (bar)	Typoszereg	Średnica zew. rury Ø (mm)	G1 + G2
HFM T HL 04	315	L	6	M 12 x 1,5
HFM T HL 06	315	L	8	M 14 x 1,5
HFM T HL 08	315	L	10	M 16 x 1,5
HFM T HL 10	315	L	12	M 18 x 1,5
HFM T HL 13	315	L	15	M 22 x 1,5
HFM T HL 16	315	L	18	M 26 x 1,5
HFM T HL 20	160	L	22	M 30 x 2
HFM T HL 25	160	L	28	M 36 x 2
HFM T HL 32	160	L	35	M 45 x 2
HFM T HL 40	160	L	42	M 52 x 2
HFM T HS 03	630	S	6	M 14 x 1,5
HFM T HS 04	630	S	8	M 16 x 1,5
HFM T HS 06	630	S	10	M 18 x 1,5
HFM T HS 08	630	S	12	M 20 x 1,5
HFM T HS 10	630	S	14	M 22 x 1,5
HFM T HS 13	400	S	16	M 24 x 1,5
HFM T HS 16	400	S	20	M 30 x 2
HFM T HS 20	400	S	25	M 36 x 2
HFM T HS 25	400	S	30	M 42 x 2
HFM T HS 32	315	S	38	M 52 x 2