



HFM T HL S / HFM T HS S - Measuring connection, plug-in series

Connection 1 + 2
Sealing form 1 + 2
Connection 3
Construction Standard

Included in scope of supply
Temp. min.
Temp. max.
Material
Surface

metric cylindrical outer thread
 24° inner cone
 Plug connection for measuring technology
 T shaped
 DIN 2353
 ISO 8434-1
 with locking connector and retaining pin
 -20 °C
 100 °C
 Steel
 electro galvanised

| Name | Ciśn. rob. (bar) | Typszereg | Średnica zew. rury Ø (mm) | G1 + G2 |
|---------------|------------------|-----------|---------------------------|------------|
| HFM T HL 04 S | 315 | L | 6 | M 12 x 1,5 |
| HFM T HL 06 S | 315 | L | 8 | M 14 x 1,5 |
| HFM T HL 08 S | 315 | L | 10 | M 16 x 1,5 |
| HFM T HL 10 S | 315 | L | 12 | M 18 x 1,5 |
| HFM T HL 13 S | 315 | L | 15 | M 22 x 1,5 |
| HFM T HL 16 S | 315 | L | 18 | M 26 x 1,5 |
| HFM T HL 20 S | 160 | L | 22 | M 30 x 2 |
| HFM T HL 25 S | 160 | L | 28 | M 36 x 2 |
| HFM T HL 32 S | 160 | L | 35 | M 45 x 2 |
| HFM T HL 40 S | 160 | L | 42 | M 52 x 2 |
| HFM T HS 03 S | 630 | S | 6 | M 14 x 1,5 |
| HFM T HS 04 S | 400 | S | 8 | M 16 x 1,5 |
| HFM T HS 06 S | 400 | S | 10 | M 18 x 1,5 |
| HFM T HS 08 S | 400 | S | 12 | M 20 x 1,5 |
| HFM T HS 10 S | 400 | S | 14 | M 22 x 1,5 |
| HFM T HS 13 S | 400 | S | 16 | M 24 x 1,5 |
| HFM T HS 16 S | 400 | S | 20 | M 30 x 2 |
| HFM T HS 20 S | 400 | S | 25 | M 36 x 2 |
| HFM T HS 25 S | 400 | S | 30 | M 42 x 2 |
| HFM T HS 32 S | 315 | S | 38 | M 52 x 2 |