



BR - Spiral support ring BR

Design
Operating pressure
Colour
Temp. min.
Temp. max.
Media

Support ring
 up to 500 bar
 white
 -200 °C
 260 °C
 Mineral oils
 HFA, HFB, HFC, HFD, steam
 PTFE

Material

| Name | DN | Size | Screw |
|-------------|----|------|-------|
| PN 06 BR | 6 | 4 | 1/4" |
| PN 06 BR 04 | 6 | 4 | 1/8" |
| PN 06 BR 10 | 6 | 4 | 3/8" |
| PN 08 BR 04 | 8 | 5 | 1/8" |
| PN 08 BR 06 | 8 | 5 | 1/4" |
| PN 08 BR 10 | 8 | 5 | 3/8" |
| PN 10 BR 06 | 10 | 6 | 1/4" |
| PN 10 BR | 10 | 6 | 3/8" |
| PN 10 BR 13 | 10 | 6 | 1/2" |
| PN 13 BR 06 | 13 | 8 | 1/4" |
| PN 13 BR 10 | 13 | 8 | 3/8" |
| PN 13 BR | 13 | 8 | 1/2" |
| PN 13 BR 16 | 13 | 8 | 5/8" |
| PN 16 BR | 16 | 10 | 5/8" |
| PN 16 BR 20 | 16 | 10 | 3/4" |
| PN 20 BR | 20 | 12 | 3/4" |
| PN 20 BR 25 | 20 | 12 | 1" |
| PN 25 BR | 25 | 16 | 1" |