


## 1SN - HD hose



### Application

Low and medium high pressure circuits  
 Return hoses

### Standard Inner layer Insert Outer layer

EN 853 1 SN  
 oil resistant synthetic rubber  
 one high tensile steel wire braided insert  
 synthetic rubber with high temperature,  
 ozone and weather resistance

### Colour Temp. min. Temp. max. Elongation Media

black  
 -40 °C  
 100 °C  
 + 2 % to - 4 %  
 Mineral oil  
 Polyglycol based oil  
 Water (0°C to + 70°C)  
 Water-oil emulsions

Name	DN	Ø wew. (mm)	Ø zew. (mm)	Ciśn. rob. (bar)	Ciśnienie testowe	Ciśn. rozrywające (bar)	R. min.
1 SN DN 04	4	4,8	11,8	250	600	1000	90
1 SN DN 06	6	6,3	14,0	225	540	900	100
1 SN DN 08	8	8,0	15,5	215	510	850	115
1 SN DN 10	10	9,5	17,5	180	435	720	130
1 SN DN 12	13	12,7	21,0	160	385	640	180
1 SN DN 16	16	16,0	24,0	130	315	520	200
1 SN DN 19	20	19,0	28,0	105	255	420	240
1 SN DN 25	25	25,3	36,0	88	210	350	300
1 SN DN 31	32	32,0	43,5	63	150	250	420
1 SN DN 38	40	38,1	50,6	50	120	200	500
1 SN DN 50	50	50,8	64	40	96	160	630