

TF CONVO - pipes and hoses made of fluorinated notched



Excellent chemical resistance to virtually all chemicals and solvents were used with the exception of fluorine in gaseous form, molten alkali metals, chlorine trifluoride and oxygen difluoride.

It is completely resistant to UV radiation, oxygen, ozone and light.

Very low coefficient of friction from 0.02 to 0.2.

Cover: standard cover is a single braided stainless steel AISI 304.

Temperature range: operating temperature of -60°C to + 260°C.

NOTE: If operating temperatures above 120 ° C maximum pressure ROB. given in the table should be reduced by 1% for each degree increase in temperature.

Name	DN	Ø wew. (mm)	Ø zew. (mm)	Ciśn. rob. (bar)	Ciśn. rozrywające (bar)	R. min.
TF 106 C	6	6,73-7,49	11,94-12,70	172	517	17,8
TF 108 C	8	-	-	150	483	18,5
TF 110 C	10	9,14-9,91	14,73-15,75	138	414	20,3
TF 113 C	13	12,45-13,21	18,29-19,30	103	310	25,4
TF 116 C	16	15,37-14,38	21,59-22,61	83	248	50,8
TF 120 C	20	18,54-19,56	24,00-25,27	69	207	63,5
TF 125 C	25	24,89-26,16	32,13-33,56	46	138	88,9
TF 132 C	32	31,00-33,00	39,00-42,00	34	103	127
TF 140 C	40	37,50-40,50	46,99-49,20	30	90	152,4
TF 150 C	50	48,00-52,00	58,67-59,70	23	69	200