



FBSB - Heat protection hose, silicate, silicone

Application

Foundries, steelworks, glassworks, shipyards etc.

Application

as contact protection for hot and cold hoses

Colour

smooth, rust red

Temp. min.

-65 °C

Temp. max.

260 °C

Temp.

from inner diameter 6 mm to 127 mm:
1090 °C for 15-20 min. ; 1650 °C for 15-30 sec.

Material

Calcium silicate fibres with a silicone cover

Name	Ø wew. (mm)
FBSB 006	6,0
FBSB 008	8,0
FBSB 010	10,0
FBSB 013	13,0
FBSB 016	16,0
FBSB 019	19,0
FBSB 022	22,0
FBSB 025	25,0
FBSB 029	29,0
FBSB 032	32,0
FBSB 035	35,0
FBSB 038	38,0
FBSB 041	41,0
FBSB 044	44,0
FBSB 051	51,0
FBSB 057	57,0
FBSB 064	64,0
FBSB 070	70,0
FBSB 076	76,0
FBSB 083	83,0
FBSB 089	89,0
FBSB 095	95,0
FBSB 102	102,0
FBSB 114	114,0
FBSB 127	127,0
FBSB 160	160,0
FBSB 170	170,0
FBSB 180	180,0

Name	Ø wew. (mm)
FBSB 200	200,0
FBSB 220	220,0
FBSB 250	250,0
FBSB 300	300,0