



## Spigot NW 5, with external thread, brass

|  |  |
|--|--|
| Pressure:  | from 0 to 35 bar the maximum static pressure |
| The temperature of the medium and the environment: | from -20 ° C to + 100 ° C                    |
| Building:  | Brass  |
| The spring latch ring, balls:                      | stainless steel                              |
| Sealing:   | NBR  |

| Name       | Złącze          | SW | l    |
|------------|-----------------|----|------|
| 243.031    | G1/8 zewnętrzny | 14 | 25   |
| 243.032    | G1/4 zewnętrzny | 17 | 27,5 |
| 243.032/S  | G3/8 zewnętrzny | 19 | 27,5 |
| ESM 18 NA  | G1/8 zewnętrzny | 13 | 25   |
| ESM 14 NA  | G1/4 zewnętrzny | 17 | 27,5 |
| ESM 38 NA  | G3/8 wewnętrzny | 17 | 27,5 |
| ESM 101 NA | M 10x1          | 13 | 26   |
| ESM 121 NA | M 12x1,5        | 17 | 28,5 |
| ESM 141 NA | M 14x1,5        | 17 | 28,5 |
| ESM 18 NAS | G1/8 zewnętrzny | 13 | 25   |
| ESM 14 NAS | G1/4 zewnętrzny | 17 | 27,5 |