



## Plastic manometer with single scale, connection bottom

Execution:

Application:

Accuracy:

Housing:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and m  
 a media that do not attack

1.6

Plastics

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Średnica w mm	Zakres ciśnień
110.31-K	40	0 - 1,6 bar
110.32-K	40	0 - 2,5 bar
110.33-K	40	0 - 4,0 bar
110.34-K	40	0 - 6,0 bar
110.35-K	40	0 - 10,0 bar
110.36-K	40	0 - 16,0 bar
110.37-K	40	0 - 25,0 bar
110.38-K	40	0 - 40,0 bar
101-K	50	0 - 1,0 bar
102-K	50	0 - 1,6 bar
103-K	50	0 - 2,5 bar
104-K	50	0 - 4,0 bar
105-K	50	0 - 6,0 bar
106-K	50	0 - 10,0 bar
107-K	50	0 - 16,0 bar
108-K	50	0 - 25,0 bar
109-K	50	0 - 40,0 bar
110/1-K	50	0 - 100,0 bar
110/2-K	50	0 - 160,0 bar
110-K	50	0 - 60,0 bar
111-K	63	0 - 0,6 bar
112-K	63	0 - 1,0 bar
113-K	63	0 - 1,6 bar

<b>Name</b>	<b>Średnica w mm</b>	<b>Zakres ciśnień</b>
114-K	63	0 - 2,5 bar
115-K	63	0 - 4,0 bar
116-K	63	0 - 6,0 bar
117-K	63	0 - 10,0 bar
118-K	63	0 - 16,0 bar
119-K	63	0 - 25,0 bar
120-K	63	0 - 40,0 bar
121-K	63	0 - 60,0 bar
122-K	63	0 - 100,0 bar
123-K	63	0 - 160,0 bar
124-K	63	0 - 250,0 bar
125-K	63	0 - 315,0 bar
126-K	63	0 - 400,0 bar