



Plastic manometer with single scale, rear connection

Execution:

Application:

Accuracy:

Housing:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, non-corrosive media that do not attack

1.6

Plastics

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Screw	Średnica w mm	Zakres ciśnień
110.42-K	G1/8	40	0 - 1,6 bar
110.43-K	G1/8	40	0 - 2,5 bar
110.44-K	0 - 4,0 bar	40	G1/8
110.45-K	0 - 6,0 bar	40	G1/8
110.46-K	0 - 10,0 bar	40	G1/8
110.47-K	0 - 16,0 bar	40	G1/8
110.48-K	0 - 25,0 bar	40	G1/8
110.49-K	0 - 40,0 bar	40	G1/8
201-K	0 - 1,0 bar	50	G1/4
202-K	0 - 1,6 bar	50	G1/4
203-K	0 - 2,5 bar	50	G1/4
204-K	0 - 4,0 bar	50	G1/4
205-K	0 - 6,0 bar	50	G1/4
206-K	0 - 10,0 bar	50	G1/4
207-K	0 - 16,0 bar	50	G1/4
208-K	0 - 25,0 bar	50	G1/4
209-K	0 - 40,0 bar	50	G1/4
210-K	0 - 60,0 bar	50	G1/4
210/1-K	0 - 100,0 bar	50	G1/4
211-K	0 - 0,6 bar	63	G1/4
212-K	0 - 1,0 bar	63	G1/4
213-K	0 - 1,6 bar	63	G1/4
214-K	0 - 2,5 bar	63	G1/4

Name	Screw	Średnica w mm	Zakres ciśnień
215-K	0 - 4,0 bar	63	G1/4
216-K	0 - 6,0 bar	63	G1/4
217-K	0 - 10,0 bar	63	G1/4
218-K	0 - 16,0 bar	63	G1/4
219-K	0 - 25,0 bar	63	G1/4
220-K	0 - 40,0 bar	63	G1/4
221-K	0 - 60,0 bar	63	G1/4
222-K	0 - 100,0 bar	63	G1/4
223-K	0 - 160,0 bar	63	G1/4
224-K	0 - 250,0 bar	63	G1/4
225-K	0 - 315,0 bar	63	G1/4
226-K	0 - 400,0 bar	63	G1/4