



Pressure gauge plastic dual scale, connection bottom

Execution:

Application:

Accuracy:

Housing:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack

1.6

Plastics

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Zakres ciśnień	Średnica w mm	Screw
110.32-KD	0 - 2,5 bar/ 36 psi	40	G1/8
110.33-KD	0 - 4,0 bar/ 60 psi	40	G1/8
110.34-KD	0 - 6,0 bar/ 90 psi	40	G1/8
110.35-KD	0 - 10,0 bar/ 145 psi	40	G1/8
110.36-KD	0 - 16,0 bar/ 235 psi	40	G1/8
110.37-KD	0 - 25,0 bar/ 360 psi	40	G1/8
103-KD	0 - 2,5 bar/ 36 psi	50	G1/4
104-KD	0 - 4,0 bar/ 60 psi	50	G1/4
105-KD	0 - 6,0 bar/ 90 psi	50	G1/4
106-KD	0 - 10,0 bar/ 145 psi	50	G1/4
107-KD	0 - 16,0 bar/ 235 psi	50	G1/4
108-KD	0 - 25,0 bar/ 360 psi	50	G1/4
114-KD	0 - 2,5 bar/ 36 psi	63	G1/4
115-KD	0 - 4,0 bar/ 60 psi	63	G1/4
116-KD	0 - 6,0 bar/ 90 psi	63	G1/4
117-KD	0 - 10,0 bar/ 145 psi	63	G1/4
118-KD	0 - 16,0 bar/ 235 psi	63	G1/4
119-KD	0 - 25,0 bar/ 360 psi	63	G1/4