



Pressure gauge plastic dual scale, rear connection

Execution:

Application:

Accuracy:

Housing:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack

1.6

Plastics

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Zakres ciśnień	Średnica w mm	Screw
110.43-KD	0 - 2,5 bar/ 36 psi	40	G1/8
214-KD	0 - 2,5 bar/ 36 psi	63	G1/4
110.44-KD	0 - 4,0 bar/ 60 psi	40	G1/8
110.45-KD	0 - 6,0 bar/ 90 psi	40	G1/8
110.46-KD	0 - 10,0 bar/ 145 psi	40	G1/8
110.47-KD	0 - 16,0 bar/ 235 psi	40	G1/8
110.48-KD	0 - 25,0 bar/ 360 psi	40	G1/8
110.02-KD	0 - 6,0 bar/ 90 psi	40	G1/4
110.03-KD	0 - 10,0 bar/ 145 psi	40	G1/4
203-KD	0 - 2,5 bar/ 36 psi	50	G1/4
204-KD	0 - 4,0 bar/ 60 psi	50	G1/4
205-KD	0 - 6,0 bar/ 90 psi	50	G1/4
206-KD	0 - 10,0 bar/ 145 psi	50	G1/4
207-KD	0 - 16,0 bar/ 235 psi	50	G1/4
208-KD	0 - 25,0 bar/ 360 psi	50	G1/4
215-KD	0 - 4,0 bar/ 60 psi	63	G1/4
216-KD	0 - 6,0 bar/ 90 psi	63	G1/4
217-KD	0 - 10,0 bar/ 145 psi	63	G1/4
218-KD	0 - 16,0 bar/ 235 psi	63	G1/4
219-KD	0 - 25,0 bar/ 360 psi	63	G1/4