



## Standard pressure gauge, dual scale, rear connection, accuracy class 2.5

Execution:

Application:

Accuracy:

Housing:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack brass

1.6

Plastics

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Zakres ciśnień	Średnica w mm	Screw
M40A.PL001G18	-1 / 0,0 bar	40	G1/8
M40A.PL002G18	0 - 1,6 bar	40	G1/8
M40A.PL003G18	0 - 2,5 bar	40	G1/8
M40A.PL004G18	0 - 4,0 bar	40	G1/8
M40A.PL006G18	0 - 6,0 bar	40	G1/8
M40A.PL010G18	0 - 10,0 bar	40	G1/8
M40A.PL012G18	0 - 12,0 bar	40	G1/8
M40A.PL016G18	0 - 16,0 bar	40	G1/8
M50A.PL006G14	0 - 6,0 bar	50	G1/4
M50A.PL010G14	0 - 10,0 bar	50	G1/4
M50A.PL012G14	0 - 12,0 bar	50	G1/4
M50A.PL016G14	0 - 16,0 bar	50	G1/4
M63A.PL004G14	0 - 4,0 bar	63	G1/4
M63A.PL006G14	0 - 6,0 bar	63	G1/4
M63A.PL010G14	0 - 10,0 bar	63	G1/4
M63A.PL012G14	0 - 12,0 bar	63	G1/4
M63A.PL016G14	0 - 16,0 bar	63	G1/4