



Metal manometer with single scale, connection bottom

Execution:

Application:

Accuracy:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack brass

1.6

Housing:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Steel plate

transparent plastic

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Zakres ciśnień	Średnica w mm	Screw
110.31	0 - 1,6 bar	40	G1/8
110.32	0 - 2,5 bar	40	G1/8
110.33	0 - 4,0 bar	40	G1/8
110.34	0 - 6,0 bar	40	G1/8
110.35	0 - 10,0 bar	40	G1/8
110.36	0 - 16,0 bar	40	G1/8
110.37	0 - 25,0 bar	40	G1/8
110.38	0 - 40,0 bar	40	G1/8
101	0 - 1,0 bar	50	G1/4
102	0 - 1,6 bar	50	G1/4
103	0 - 2,5 bar	50	G1/4
104	0 - 4,0 bar	50	G1/4
105	0 - 6,0 bar	50	G1/4
106	0 - 10,0 bar	50	G1/4
107	0 - 16,0 bar	50	G1/4
108	0 - 25,0 bar	50	G1/4
109	0 - 40,0 bar	50	G1/4
110	0 - 60,0 bar	50	G1/4
110/1	0 - 100,0 bar	50	G1/4
110/2	0 - 160,0 bar	50	G1/4
111	0 - 0,6 bar	63	G1/4
112	0 - 1,0 bar	63	G1/4
113	0 - 1,6 bar	63	G1/4

Name	Zakres ciśnień	Średnica w mm	Screw
114	0 - 2,5 bar	63	G1/4
115	0 - 4,0 bar	63	G1/4
116	0 - 6,0 bar	63	G1/4
117	0 - 10,0 bar	63	G1/4
118	0 - 16,0 bar	63	G1/4
119	0 - 25,0 bar	63	G1/4
120	0 - 40,0 bar	63	G1/4
121	0 - 60,0 bar	63	G1/4
122	0 - 100,0 bar	63	G1/4
123	0 - 160,0 bar	63	G1/4
124	0 - 250,0 bar	63	G1/4
125	0 - 315,0 bar	63	G1/4
126	0 - 400,0 bar	63	G1/4