



Metal manometer with single scale, rear connection

Execution:

Application:

Accuracy:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, non-corrosive media that do not attack the Bourdon tube

1.6

Housing:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Steel plate

transparent plastic

Brass

max 60 ° C

from -20 ° C to + 60°

Name	Zakres ciśnień	Średnica w mm	Screw
110.42	0 - 1,6 bar	40	G1/8
110.43	0 - 2,5 bar	40	G1/8
110.44	0 - 4,0 bar	40	G1/8
110.45	0 - 6,0 bar	40	G1/8
110.46	0 - 10,0 bar	40	G1/8
110.47	0 - 16,0 bar	40	G1/8
110.48	0 - 25,0 bar	40	G1/8
110.49	0 - 40,0 bar	40	G1/8
201	0 - 1,0 bar	50	G1/4
202	0 - 1,6 bar	50	G1/4
203	0 - 2,5 bar	50	G1/4
204	0 - 4,0 bar	50	G1/4
205	0 - 6,0 bar	50	G1/4
206	0 - 10,0 bar	50	G1/4
207	0 - 16,0 bar	50	G1/4
208	0 - 25,0 bar	50	G1/4
209	0 - 40,0 bar	50	G1/4
210	0 - 60,0 bar	50	G1/4
210/1	0 - 100,0 bar	50	G1/4
211	0 - 0,6 bar	63	G1/4
212	0 - 1,0 bar	63	G1/4
213	0 - 1,6 bar	63	G1/4
214	0 - 2,5 bar	63	G1/4

Name	Zakres ciśnień	Średnica w mm	Screw
215	0 - 4,0 bar	63	G1/4
216	0 - 6,0 bar	63	G1/4
217	0 - 10,0 bar	63	G1/4
218	0 - 16,0 bar	63	G1/4
219	0 - 25,0 bar	63	G1/4
220	0 - 40,0 bar	63	G1/4
221	0 - 60,0 bar	63	G1/4
222	0 - 100,0 bar	63	G1/4
223	0 - 160,0 bar	63	G1/4
224	0 - 250,0 bar	63	G1/4
225	0 - 315,0 bar	63	G1/4
226	0 - 400,0 bar	63	G1/4