



Pressure gauge with flanged chrome, rear connection

Execution:

Application:

Accuracy:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack brass

1.6

Hour:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Steel plate

transparent plastic

Brass

max 60 ° C

-40 to + 60°

Name	Zakres ciśnień	Średnica w mm	Screw
301/40	0 - 1,0 bar	40	G1/8
302/40	0 - 1,6 bar	40	G1/8
303/40	0 - 2,5 bar	40	G1/8
304/40	0 - 4,0 bar	40	G1/8
305/40	0 - 6,0 bar	40	G1/8
306/40	0 - 10,0 bar	40	G1/8
307/40	0 - 16,0 bar	40	G1/8
308/40	0 - 25,0 bar	40	G1/8
309/40	0 - 40,0 bar	40	G1/8
301/50	0 - 1,0 bar	50	G1/4
302/50	0 - 1,6 bar	50	G1/4
303/50	0 - 2,5 bar	50	G1/4
304/50	0 - 4,0 bar	50	G1/4
305/50	0 - 6,0 bar	50	G1/4
306/50	0 - 10,0 bar	50	G1/4
307/50	0 - 16,0 bar	50	G1/4
308/50	0 - 25,0 bar	50	G1/4
309/50	0 - 40,0 bar	50	G1/4
301/63	0 - 1,0 bar	63	G1/4
302/63	0 - 1,6 bar	63	G1/4
303/63	0 - 2,5 bar	63	G1/4
304/63	0 - 4,0 bar	63	G1/4
305/63	0 - 6,0 bar	63	G1/4

Name	Zakres ciśień	Średnica w mm	Screw
306/63	0 - 10,0 bar	63	G1/4
307/63	0 - 16,0 bar	63	G1/4
308/63	0 - 25,0 bar	63	G1/4
309/63	0 - 40,0 bar	63	G1/4