



Housing:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Pressure gauge with a black collar, rear connection

Execution:

Application:

Accuracy:

Steel plate

transparent plastic

Brass

max 60 ° C

-40 to + 60°

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack brass

1.6

Name	Zakres ciśnień	Średnica w mm	Screw
320/40	0 - 1,0 bar	40	G1/8
321/40	0 - 1,6 bar	40	G1/8
322/40	0 - 2,5 bar	40	G1/8
323/40	0 - 4,0 bar	40	G1/8
324/40	0 - 6,0 bar	40	G1/8
325/40	0 - 10,0 bar	40	G1/8
326/40	0 - 16,0 bar	40	G1/8
327/40	0 - 25,0 bar	40	G1/8
328/40	0 - 40,0 bar	40	G1/8
320/50	0 - 1,0 bar	50	G1/4
321/50	0 - 1,6 bar	50	G1/4
322/50	0 - 2,5 bar	50	G1/4
323/50	0 - 4,0 bar	50	G1/4
324/50	0 - 6,0 bar	50	G1/4
325/50	0 - 10,0 bar	50	G1/4
326/50	0 - 16,0 bar	50	G1/4
327/50	0 - 25,0 bar	50	G1/4
328/50	0 - 40,0 bar	50	G1/4
329/50	0 - 60,0 bar	50	G1/4
320/63	0 - 1,0 bar	63	G1/4
321/63	0 - 1,6 bar	63	G1/4
322/63	0 - 2,5 bar	63	G1/4
323/63	0 - 4,0 bar	63	G1/4

Name	Zakres ciśień	Średnica w mm	Screw
324/63	0 - 6,0 bar	63	G1/4
325/63	0 - 10,0 bar	63	G1/4
326/63	0 - 16,0 bar	63	G1/4
327/63	0 - 25,0 bar	63	G1/4
328/63	0 - 40,0 bar	63	G1/4
329/63	0 - 60,0 bar	63	G1/4