



Glycerine pressure gauge, metal, connection bottom

Execution:	Bourdon tube pressure gauge
Application:	gases, liquids of low and medium viscosity, media that do not attack metal
Accuracy:	1.6 (for diameter 63 mm), 1.0 (for diameter 100 mm)
Housing:	Stainless steel
Glass:	Acrylic
Connection:	Brass <100 bar Stainless steel => 100 bar
The temperature of the medium:	max 60 ° C
Ambient temperature:	from -20°C to + 60°C

Name	Screw	Średnica w mm	Zakres ciśnień
701	G1/4	63	0 - 0,6 bar
702	G1/4	63	0 - 1,0 bar
703	G1/4	63	0 - 1,6 bar
704	G1/4	63	0 - 2,5 bar
705	G1/4	63	0 - 4,0 bar
706	G1/4	63	0 - 6,0 bar
707	G1/4	63	0 - 10,0 bar
708	G1/4	63	0 - 16,0 bar
709	G1/4	63	0 - 25,0 bar
710	G1/4	63	0 - 40,0 bar
711	G1/4	63	0 - 60,0 bar
712	G1/4	63	0 - 100,0 bar
713	G1/4	63	0 - 160,0 bar
714	G1/4	63	0 - 250,0 bar
715	G1/4	63	0 - 400,0 bar
716	G1/4	63	0 - 600,0 bar
721	G1/2	100	0 - 0,6 bar
722	G1/2	100	0 - 1,0 bar
723	G1/2	100	0 - 1,6 bar
724	G1/2	100	0 - 2,5 bar
725	G1/2	100	0 - 4,0 bar
726	G1/2	100	0 - 6,0 bar

Name	Screw	Średnica w mm	Zakres ciśnień
727	G1/2	100	0 - 10,0 bar
728	G1/2	100	0 - 16,0 bar
729	G1/2	100	0 - 25,0 bar
730	G1/2	100	0 - 40,0 bar
731	G1/2	100	0 - 60,0 bar
732	G1/2	100	0 - 100,0 bar
733	G1/2	100	0 - 160,0 bar
734	G1/2	100	0 - 250,0 bar
735	G1/2	100	0 - 400,0 bar
736	G1/2	100	0 - 600,0 bar
737	G1/2	100	0 - 1000,0 bar
741	G1/2	160	0 - 0,6 bar
742	G1/2	160	0 - 1,0 bar
743	G1/2	160	0 - 1,6 bar
744	G1/2	160	0 - 2,5 bar
745	G1/2	160	0 - 4,0 bar
746	G1/2	160	0 - 6,0 bar
747	G1/2	160	0 - 10,0 bar
748	G1/2	160	0 - 16,0 bar
749	G1/2	160	0 - 25,0 bar
750	G1/2	160	0 - 40,0 bar
751	G1/2	160	0 - 60,0 bar
752	G1/2	160	0 - 100,0 bar
753	G1/2	160	0 - 160,0 bar
754	G1/2	160	0 - 250,0 bar
755	G1/2	160	0 - 400,0 bar
756	G1/2	160	0 - 600,0 bar