



Vacuum gauge glycerin, metal, connection bottom

Execution:

Application:

Accuracy:

Housing:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack

1.6 (for diameter 63 mm), 1.0 (for diameter 100 mm)

Stainless steel

Acrylic

Brass <100 bar

Stainless steel => 100 bar

max 60 ° C

from -20°C to + 60°C

Name	Zakres ciśnień	Średnica w mm	Screw
700	-1 / 0,0 bar	63	G1/4
700/1	-1 / +0,6 bar	63	G1/4
700/2	-1 / +1,5 bar	63	G1/4
700/3	-1 / +3,0 bar	63	G1/4
700/4	-1 / +5,0 bar	63	G1/4
700/5	-1 / +9,0 bar	63	G1/4
700/6	-1 / +15,0 bar	63	G1/4
720	-1 / 0,0 bar	100	G1/2
720/1	-1 / +0,6 bar	100	G1/2
720/2	-1 / +1,5 bar	100	G1/2
720/3	-1 / +3,0 bar	100	G1/2
720/4	-1 / +5,0 bar	100	G1/2
720/5	-1 / +9,0 bar	100	G1/2
720/6	-1 / +15,0 bar	100	G1/2
740	-1 / 0,0 bar	160	G1/2
740/1	-1 / +0,6 bar	160	G1/2
740/2	-1 / +1,5 bar	160	G1/2
740/3	-1 / +3,0 bar	160	G1/2
740/4	-1 / +5,0 bar	160	G1/2
740/5	-1 / +9,0 bar	160	G1/2
740/6	-1 / +15,0 bar	160	G1/2

