



Glycerine pressure gauge, metal, rear connection

Execution:

Application:

Accuracy:

Housing:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, media that do not attack

1.6 (for diameter 63 mm), 1.0 (for diameter 100 mm)

Stainless steel

Acrylic

Brass <100 bar

Stainless steel => 100 bar

max 60 ° C

from -20°C to + 60°C

Name	Zakres ciśnień	Średnica w mm	Screw
801	0 - 0,6 bar	63	G1/4
802	0 - 1,0 bar	63	G1/4
803	0 - 1,6 bar	63	G1/4
804	0 - 2,5 bar	63	G1/4
805	0 - 4,0 bar	63	G1/4
806	0 - 6,0 bar	63	G1/4
807	0 - 10,0 bar	63	G1/4
808	0 - 16,0 bar	63	G1/4
809	0 - 25,0 bar	63	G1/4
810	0 - 40,0 bar	63	G1/4
811	0 - 60,0 bar	63	G1/4
812	0 - 100,0 bar	63	G1/4
813	0 - 160,0 bar	63	G1/4
814	0 - 250,0 bar	63	G1/4
815	0 - 400,0 bar	63	G1/4
816	0 - 600,0 bar	63	G1/4
821	0 - 1,0 bar	100	G1/2
822	0 - 1,6 bar	100	G1/2
823	0 - 2,5 bar	100	G1/2
824	0 - 4,0 bar	100	G1/2
825	0 - 6,0 bar	100	G1/2
826	0 - 10,0 bar	100	G1/2

Name	Zakres ciśień	Średnica w mm	Screw
827	0 - 16,0 bar	100	G1/2
828	0 - 25,0 bar	100	G1/2
829	0 - 40,0 bar	100	G1/2
830	0 - 60,0 bar	100	G1/2
831	0 - 100,0 bar	100	G1/2
832	0 - 160,0 bar	100	G1/2
833	0 - 250,0 bar	100	G1/2
834	0 - 400,0 bar	100	G1/2
835	0 - 600,0 bar	100	G1/2