



Glycerine pressure gauge, plastic, dual scale, connection bottom

Execution:

Application:

Accuracy:

Housing:

Glass:

Connection:

The temperature of the medium:

Ambient temperature:

Bourdon tube pressure gauge

gases, liquids of low and medium viscosity, and media that do not attack

2.5

Plastic, black

PMMA

Brass

max 60 ° C

from -20°C to + 60°C

| Name | Zakres ciśnień | Średnica w mm | Screw |
|-------|----------------|---------------|-------|
| 702-K | 0 - 1,0 bar | 63 | G1/4 |
| 703-K | 0 - 1,6 bar | 63 | G1/4 |
| 704-K | 0 - 2,5 bar | 63 | G1/4 |
| 705-K | 0 - 4,0 bar | 63 | G1/4 |
| 706-K | 0 - 6,0 bar | 63 | G1/4 |
| 707-K | 0 - 10,0 bar | 63 | G1/4 |
| 708-K | 0 - 16,0 bar | 63 | G1/4 |
| 709-K | 0 - 25,0 bar | 63 | G1/4 |
| 710-K | 0 - 40,0 bar | 63 | G1/4 |
| 711-K | 0 - 60,0 bar | 63 | G1/4 |
| 712-K | 0 - 100,0 bar | 63 | G1/4 |
| 713-K | 0 - 160,0 bar | 63 | G1/4 |
| 714-K | 0 - 250,0 bar | 63 | G1/4 |
| 715-K | 0 - 400,0 bar | 63 | G1/4 |