



Natablicowy glycerine pressure gauge, chrome plated, polished

Execution:	Bourdon tube pressure gauge
Application:	gases, liquids of low and medium viscosity, media that do not attack brass
Accuracy:	1.6 (for diameter 63 mm), 1.0 (for diameter 100 mm)
Housing:	Hot-pressed brass
Glass:	Acrylic
Connection:	Brass
The temperature of the medium:	max 60 ° C
Ambient temperature:	from -20°C to + 60°C

Name	Zakres ciśnień	Średnica w mm	Screw
900/1	0 - 2,5 bar	63	G1/4
901	0 - 4,0 bar	63	G1/4
902	0 - 6,0 bar	63	G1/4
903	0 - 10,0 bar	63	G1/4
904	0 - 16,0 bar	63	G1/4
905	0 - 25,0 bar	63	G1/4
906	0 - 40,0 bar	63	G1/4
907	0 - 60,0 bar	63	G1/4
908	0 - 100,0 bar	63	G1/4
909	0 - 160,0 bar	63	G1/4
910	0 - 250,0 bar	63	G1/4
911	0 - 400,0 bar	63	G1/4
951	0 - 1,0 bar	100	G1/2
952	0 - 1,6 bar	100	G1/2
953	0 - 2,5 bar	100	G1/2
954	0 - 4,0 bar	100	G1/2
955	0 - 6,0 bar	100	G1/2
956	0 - 10,0 bar	100	G1/2
957	0 - 16,0 bar	100	G1/2
958	0 - 25,0 bar	100	G1/2
959	0 - 40,0 bar	100	G1/2
960	0 - 60,0 bar	100	G1/2

Name	Zakres ciśień	Średnica w mm	Screw
961	0 - 100,0 bar	100	G1/2
962	0 - 160,0 bar	100	G1/2
963	0 - 250,0 bar	100	G1/2
964	0 - 400,0 bar	100	G1/2
965	0 - 600,0 bar	100	G1/2