



Gauge natablicowy glycerine, with the mounting element

Execution:	Bourdon tube pressure gauge
Application:	gases, liquids of low and medium pressure, media that do not attack brass
Accuracy:	1.6 (for diameter 63 mm), 1.0 (for diameter 100 mm)
Housing:	Hot-pressed brass
Glass:	Acrylic
Connection:	Brass
The temperature of the medium:	max 60 ° C
Ambient temperature:	from -20°C to + 60°C

Name	Zakres ciśnień	Średnica w mm	Screw
1002	0 - 1,6 bar	63	G1/4
1003	0 - 2,5 bar	63	G1/4
1004	0 - 4,0 bar	63	G1/4
1005	0 - 6,0 bar	63	G1/4
1006	0 - 10,0 bar	63	G1/4
1007	0 - 16,0 bar	63	G1/4
1008	0 - 25,0 bar	63	G1/4
1009	0 - 40,0 bar	63	G1/4
1010	0 - 60,0 bar	63	G1/4
1011	0 - 100,0 bar	63	G1/4
1012	0 - 160,0 bar	63	G1/4
1013	0 - 250,0 bar	63	G1/4
1014	0 - 400,0 bar	63	G1/4
1015	0 - 600,0 bar	63	G1/4
1022	0 - 1,6 bar	100	G1/2
1023	0 - 2,5 bar	100	G1/2
1024	0 - 4,0 bar	100	G1/2
1025	0 - 6,0 bar	100	G1/2
1026	0 - 10,0 bar	100	G1/2
1027	0 - 16,0 bar	100	G1/2
1028	0 - 25,0 bar	100	G1/2
1029	0 - 40,0 bar	100	G1/2

Name	Zakres ciśień	Średnica w mm	Screw
1030	0 - 60,0 bar	100	G1/2
1031	0 - 100,0 bar	100	G1/2
1032	0 - 160,0 bar	100	G1/2
1033	0 - 250,0 bar	100	G1/2
1034	0 - 400,0 bar	160	G1/2
1035	0 - 600,0 bar	100	G1/2