



## Contact manometer contact with a magnetic contact spring

Execution:

contact manometer Bourdon contacts (contact type 821)

Application:

contact manometers gas liquids of non-crystallizing of the noble alloys

Accuracy:

1.0

Housing:

Stainless steel 1.4301

Glass:

Thin glass

Connection:

Brass (<100 bar)  
 Stainless steel 1.4301 (> 100 bar)

The temperature of the medium:

max 80 ° C

Ambient temperature:

from -20°C to + 70°C

Name	Zakres ciśnień	Średnica w mm	Screw
2201	0 - 2,5 bar	100	G1/2
2202	0 - 4,0 bar	100	G1/2
2203	0 - 6,0 bar	100	G1/2
2204	0 - 10,0 bar	100	G1/2
2205	0 - 16,0 bar	100	G1/2
2206	0 - 25,0 bar	100	G1/2
2207	0 - 40,0 bar	100	G1/2
2208	0 - 60,0 bar	100	G1/2
2209	0 - 100,0 bar	100	G1/2
2210	0 - 160,0 bar	100	G1/2
2211	0 - 250,0 bar	100	G1/2
2212	0 - 400,0 bar	100	G1/2
3301	0 - 1,0 bar	160	G1/2
3303	0 - 6,0 bar	160	G1/2
3304	0 - 10,0 bar	160	G1/2
3305	0 - 16,0 bar	160	G1/2
3307	0 - 40,0 bar	160	G1/2
3313	0 - 600,0 bar	160	G1/2