



Precision manometer, connection bottom

| | |
|--------------------------------|---|
| Execution: | pressure gauge Bourdon tu |
| Application: | low and medium viscous a that do not attack copper a |
| Accuracy: | 0.6 |
| Housing: | CrNi-steel |
| Glass: | Smooth glass |
| Connection: | Brass (<100 bar) Stainless steel (> 100 bar) |
| The temperature of the medium: | max 80 ° C |
| Ambient temperature: | from -40°C to + 60°C |

| Name | Zakres ciśnień | Dokładność | Średnica w mm | Screw |
|------|----------------|------------|---------------|-------|
| 1159 | 0 - 0,6 bar | 0,005 | 100 | G1/2 |
| 1160 | 0 - 1,0 bar | 0,005 | 100 | G1/2 |
| 1161 | 0 - 1,6 bar | 0,010 | 100 | G1/2 |
| 1162 | 0 - 2,5 bar | 0,020 | 100 | G1/2 |
| 1163 | 0 - 4,0 bar | 0,020 | 100 | G1/2 |
| 1164 | 0 - 6,0 bar | 0,050 | 100 | G1/2 |
| 1165 | 0 - 10,0 bar | 0,050 | 100 | G1/2 |
| 1166 | 0 - 16,0 bar | 0,100 | 100 | G1/2 |
| 1167 | 0 - 25,0 bar | 0,200 | 100 | G1/2 |
| 1168 | 0 - 40,0 bar | 0,200 | 100 | G1/2 |
| 1169 | 0 - 60,0 bar | 0,500 | 100 | G1/2 |
| 1171 | 0 - 160,0 bar | 1,000 | 100 | G1/2 |
| 1172 | 0 - 250,0 bar | 2,000 | 100 | G1/2 |
| 1173 | 0 - 400,0 bar | 2,000 | 100 | G1/2 |