



Precision manometer, connection bottom

Execution:	pressure gauge Bourdon tu
Application:	low and medium viscous a that do not attack copper a
Accuracy:	0.6
Housing:	CrNi-steel
Glass:	Smooth glass
Connection:	Brass (<100 bar) Stainless steel (> 100 bar)
The temperature of the medium:	max 80 ° C
Ambient temperature:	from -40°C to + 60°C

Name	Zakres ciśnień	Dokładność	Średnica w mm	Screw
1159	0 - 0,6 bar	0,005	100	G1/2
1160	0 - 1,0 bar	0,005	100	G1/2
1161	0 - 1,6 bar	0,010	100	G1/2
1162	0 - 2,5 bar	0,020	100	G1/2
1163	0 - 4,0 bar	0,020	100	G1/2
1164	0 - 6,0 bar	0,050	100	G1/2
1165	0 - 10,0 bar	0,050	100	G1/2
1166	0 - 16,0 bar	0,100	100	G1/2
1167	0 - 25,0 bar	0,200	100	G1/2
1168	0 - 40,0 bar	0,200	100	G1/2
1169	0 - 60,0 bar	0,500	100	G1/2
1171	0 - 160,0 bar	1,000	100	G1/2
1172	0 - 250,0 bar	2,000	100	G1/2
1173	0 - 400,0 bar	2,000	100	G1/2