



50020 - Plug nipple Straight with external thread

| | |
|------------------------|--------------------------|
| Material: | Nickel-plated brass |
| Medium: | Compressed air, vacuum |
| Clamping ring: | Stainless steel AISI 304 |
| Locking ring: | Technopolymer |
| Gasket: | NBR 70 |
| Pressure: | max. 15 bar |
| Operating temperature: | -20°C To 80°C |

| Name | Waż | A | B | C | L | CH1 | CH2 |
|------------------|-----|----------|----|----|------|-----|-----|
| 50020 3-M5 | 3 | M5 | 4 | 8 | 19 | 8 | 2 |
| 50020 4-M5 | 4 | M5 | 4 | 8 | 21 | 10 | 2 |
| 50020 4-1/8 | 4 | 1/8 | 6 | 13 | 20 | 10 | 3 |
| 50020 4-1/4 | 4 | 1/4 | 8 | 16 | 19,5 | 16 | 3 |
| 50020 5-M5 | 5 | M5 | 4 | 8 | 23,5 | 12 | 2 |
| 50020 5-1/8 | 5 | 1/8 | 6 | 13 | 22 | 12 | 4 |
| 50020 6-M5 | 6 | M5 | 4 | 10 | 24,5 | 13 | 2 |
| 50020 6-1/8 | 6 | 1/8 | 6 | 13 | 23,5 | 13 | 4 |
| 50020 6-1/4 | 6 | 1/4 | 8 | 16 | 23,5 | 13 | 4 |
| 50020 6-3/8 | 6 | 3/8 | 9 | 20 | 25 | 13 | 4 |
| 50020 6-1/2 | 6 | 1/2 | 10 | 25 | 27 | 13 | 4 |
| 50020 8-1/8 | 8 | 1/8 | 6 | 13 | 25 | 14 | 5 |
| 50020 8-1/4 | 8 | 1/4 | 8 | 16 | 23 | 14 | 6 |
| 50020 8-3/8 | 8 | 3/8 | 9 | 20 | 24 | 14 | 6 |
| 50020 8-1/2 | 8 | 1/2 | 10 | 25 | 26,5 | 14 | 6 |
| 50020 10-1/4 | 10 | 1/4 | 8 | 16 | 30,5 | 17 | 6 |
| 50020 10-3/8 | 10 | 3/8 | 9 | 20 | 27,5 | 17 | 8 |
| 50020 10-1/2 | 10 | 1/2 | 10 | 25 | 27 | 17 | 8 |
| 50020 12-1/4 | 12 | 1/4 | 8 | 16 | 34,5 | 20 | 6 |
| 50020 12-3/8 | 12 | 3/8 | 9 | 20 | 34 | 20 | 8 |
| 50020 12-1/2 | 12 | 1/2 | 10 | 25 | 31 | 22 | 10 |
| 50020 14-3/8 | 14 | 3/8 | 9 | 20 | 35 | 21 | 10 |
| 50020 14-1/2 | 14 | 1/2 | 10 | 25 | 32 | 22 | 10 |
| 50020 6-M12X1,25 | 6 | M12x1,25 | 8 | 15 | 23,5 | 13 | 4 |
| 50020 6-M12x1,5 | 6 | M12x1,5 | 8 | 15 | 23,5 | 13 | 4 |

| Name | Waż | A | B | C | L | CH1 | CH2 |
|---------------------------------|------------|----------|----------|----------|----------|------------|------------|
| 6-M12X1,5 50020 8-M12X1,5 | 8 | M12x1,5 | 8 | 15 | 27,5 | 14 | 6 |