



50126 - rotational angle plug nipple with external thread, long

Material:	Nickel-plated brass
Medium:	Compressed air, vacuum
Clamping ring:	Stainless steel AISI 304
Locking ring:	Technopolymer
Gasket:	NBR 70
Pressure:	max. 15 bar
Operating temperature:	-20°C To 80°C

Name	L1 (mm)	L2 (mm)	D	Waż	A	B	CH1	CH2
50126 4-1/8	18	28,4	10,0	4	1/8	5.4	9	12
50126 4-1/4	18	30,1	10,0	4	1/4	7.1	9	15
50126 5-1/8	20	32,6	12,5	5	1/8	5.4	11	12
50126 6-1/8	6	1/8	5.4	21	32,6	11	12	12,5
50126 6-1/4	6	1/4	7.1	21	34,3	11	15	12,5
50126 8-1/8	8	1/8	5.4	22,8	36,6	12	12	14,5
50126 8-1/4	8	1/4	7.1	22,5	36,8	12	15	14,5
50126 8-3/8	8	3/8	8.1	22,5	38,8	12	18	14,5
50126 10-3/8	10	3/8	8.1	26,5	43,3	14	18	17,5
50126 10-1/4	10	1/4	7.1	26,5	44,0	14	16	17,5