



## 50216 - Tee T rotary plug with external thread

Material:	Nickel-plated brass
Medium:	Compressed air, vacuum
Clamping ring:	Stainless steel AISI 304
Locking ring:	Technopolymer
Gasket:	NBR 70
Pressure:	max. 15 bar
Operating temperature:	-20°C To 80°C

Name	Wąż	A	B	L1 (mm)	L2 (mm)	CH1	CH2	D
50216 3-M5	3	M5	3.6	34,0	16,8	9	8	10,0
50216 4-M5	4	M5	3.6	34,0	16,8	9	8	10,0
50216 4-1/8	4	1/8	5.4	34,0	17,1	9	13	10,0
50216 4-1/4	4	1/4	7.1	34,0	18,8	9	16	10,0
50216 5-M5	5	M5	3.6	40,0	18,3	11	11	12,5
50216 5-1/8	5	1/8	5.4	40,0	18,6	11	13	12,5
50216 6-M5	6	M5	7.1	42,0	18,4	11	11	12,5
50216 6-1/8	6	1/8	5.4	42,0	20,0	11	13	12,5
50216 6-1/4	6	1/4	7.1	42,0	22,7	11	16	12,5
50216 8-1/8	8	1/8	5.4	45,0	23,0	13	13	14,5
50216 8-1/4	8	1/4	7.1	45,0	25,0	13	16	14,5
50216 8-3/8	8	3/8	8.1	45,0	26,4	13	20	14,5
50216 8-1/2	8	1/2	9.6	45,0	26,7	13	25	14,5
50216 10-1/4	10	1/4	7.1	53,0	26,2	14	16	17,5
50216 10-3/8	10	3/8	8.1	53,0	26,2	14	20	17,5
50216 10-1/2	10	1/2	9.6	53,0	27,7	14	25	17,5
50216 12-3/8	12	3/8	8.1	62,6	28,4	16	16	21,5
50216 12-1/2	12	1/2	9.6	62,6	29,9	16	22	21,5
50216 14-3/8	14	3/8	8.1	62,6	28,4	16	20	21,5
50216 14-1/2	14	A	9.6	62,6	29,9	16	25	21,5
50216 6-M12X1	6	M12x1	7.3	42,0	20,3	11	16	12,5
50216 6-M12X1,25	6	M12x1,25	7.3	42,0	20,3	11	16	12,5
50216 6-M12X1,5	6	M12x1,5	7.3	42,0	20,3	11	16	12,5