



50226 - tee plug

| | |
|------------------------|--------------------------|
| Material: | Nickel-plated brass |
| Medium: | Compressed air, vacuum |
| Clamping ring: | Stainless steel AISI 304 |
| Locking ring: | Technopolymer |
| Gasket: | NBR 70 |
| Pressure: | max. 15 bar |
| Operating temperature: | -20°C To 80°C |

| Name | Wąż | A | B | L1 (mm) | L2 (mm) | CH1 | CH2 | D |
|------------------|-----|---------|-----|---------|---------|-----|-----|------|
| 50226 3-M5 | 3 | M5 | 3.6 | 16,5 | 16,2 | 9 | 8 | 10,0 |
| 50226 4-M5 | 4 | M5 | 3.6 | 17 | 16,1 | 9 | 8 | 10,0 |
| 50226 4-1/8 | 4 | 1/8 | 5.4 | 17 | 16,4 | 9 | 13 | 10,0 |
| 50226 4-1/4 | 4 | 1/4 | 7.1 | 17 | 18,1 | 9 | 16 | 10,0 |
| 50226 5-M5 | 5 | M5 | 3.6 | 20 | 18,3 | 11 | 11 | 12,5 |
| 50226 5-1/8 | 5 | 1/8 | 5.4 | 20 | 18,1 | 11 | 13 | 12,5 |
| 50226 6-M5 | 6 | M5 | 3.6 | 21 | 18,3 | 11 | 11 | 12,5 |
| 50226 6-1/8 | 6 | 1/8 | 5.4 | 21 | 18,1 | 11 | 13 | 12,5 |
| 50226 6-1/4 | 6 | 1/4 | 7.1 | 22,5 | 19,8 | 11 | 16 | 12,5 |
| 50226 8-1/8 | 8 | 1/8 | 5.4 | 22,5 | 21,6 | 13 | 13 | 14,5 |
| 50226 8-1/4 | 8 | 1/4 | 7.1 | 22,5 | 21,8 | 13 | 16 | 14,5 |
| 50226 8-3/8 | 8 | 3/8 | 8.1 | 26,5 | 23,8 | 13 | 20 | 14,5 |
| 50226 8-1/2 | 8 | 1/2 | 9.6 | 26,5 | 25,3 | 13 | 25 | 14,5 |
| 50226 10-1/4 | 10 | 1/4 | 7.1 | 26,5 | 25,8 | 14 | 16 | 17,5 |
| 50226 10-3/8 | 10 | 3/8 | 8.1 | 26,5 | 25,3 | 14 | 20 | 17,5 |
| 50226 10-1/2 | 10 | 1/2 | 9.6 | 26,5 | 26,8 | 14 | 25 | 17,5 |
| 50226 12-3/8 | 12 | 3/8 | 8.1 | 31,3 | 28,4 | 16 | 20 | 21,5 |
| 50226 12-1/2 | 12 | 1/2 | 9.6 | 31,3 | 29,9 | 16 | 25 | 21,5 |
| 50226 6-M12X1 | 6 | M12x1 | 7.3 | 21 | 20,0 | 11 | 16 | 12,5 |
| 50226 6-M12X1,25 | 6 | A | 7.3 | 21 | 20,0 | 11 | 16 | 12,5 |
| 50226 6-M12X1,5 | 6 | M12x1,5 | 7.3 | 21 | 20,0 | 11 | 16 | 12,5 |