



55325 - tee plug-Y rotary screw rotary

| | |
|------------------------|--------------------------|
| Material: | Nickel-plated brass |
| Medium: | Compressed air, vacuum |
| Clamping ring: | Stainless steel AISI 304 |
| Locking ring: | Technopolymer |
| Gasket: | NBR 70 |
| Pressure: | max. 15 bar |
| Operating temperature: | -20°C To 80°C |

| Name | Waż | A | B | C | L | CH1 | CH2 |
|--------------|-----|-----|----|------|------|-----|-----|
| 55325 4-M5 | 4 | M5 | 4 | 11 | 36,5 | 10 | 10 |
| 55325 4-1/8 | 4 | 1/8 | 6 | 11 | 38,5 | 10 | 13 |
| 55325 4-1/4 | 4 | 1/4 | 8 | 11 | 40,5 | 10 | 16 |
| 55325 6-1/8 | 6 | 1/8 | 6 | 13,5 | 43,5 | 12 | 13 |
| 55325 6-1/4 | 6 | 1/4 | 8 | 13,5 | 46,5 | 12 | 16 |
| 55325 8-1/8 | 8 | 1/8 | 6 | 15,5 | 47 | 14 | 13 |
| 55325 8-3/8 | 8 | 3/8 | 9 | 15,5 | 52 | 14 | 20 |
| 55325 8-1/4 | 8 | 1/4 | 8 | 15,5 | 50 | 14 | 16 |
| 55325 10-1/4 | 10 | 1/4 | 8 | 19 | 59,5 | 17 | 16 |
| 55325 10-3/8 | 10 | 3/8 | 9 | 19 | 59,5 | 17 | 20 |
| 55325 10-1/2 | 10 | 1/2 | 10 | 19 | 62 | 17 | 24 |
| 55325 12-3/8 | 12 | 3/8 | 9 | 22 | 68,5 | 20 | 20 |
| 55325 12-1/2 | 12 | 1/2 | 10 | 22 | 71 | 20 | 24 |