



55325 - tee plug-Y rotary screw rotary

Material:	Nickel-plated brass
Medium:	Compressed air, vacuum
Clamping ring:	Stainless steel AISI 304
Locking ring:	Technopolymer
Gasket:	NBR 70
Pressure:	max. 15 bar
Operating temperature:	-20°C To 80°C

Name	Waż	A	B	C	L	CH1	CH2
55325 4-M5	4	M5	4	11	36,5	10	10
55325 4-1/8	4	1/8	6	11	38,5	10	13
55325 4-1/4	4	1/4	8	11	40,5	10	16
55325 6-1/8	6	1/8	6	13,5	43,5	12	13
55325 6-1/4	6	1/4	8	13,5	46,5	12	16
55325 8-1/8	8	1/8	6	15,5	47	14	13
55325 8-3/8	8	3/8	9	15,5	52	14	20
55325 8-1/4	8	1/4	8	15,5	50	14	16
55325 10-1/4	10	1/4	8	19	59,5	17	16
55325 10-3/8	10	3/8	9	19	59,5	17	20
55325 10-1/2	10	1/2	10	19	62	17	24
55325 12-3/8	12	3/8	9	22	68,5	20	20
55325 12-1/2	12	1/2	10	22	71	20	24