



50550 - insertion sleeve-type rotary angle Banjo

Material:	Nickel-plated brass
Medium:	Compressed air, vacuum
Clamping ring:	Stainless steel AISI 304
Locking ring:	Technopolymer
Gasket:	NBR 70
Pressure:	max. 15 bar
Operating temperature:	-20°C To 80°C

Name	L1 (mm)	L2 (mm)	D	Waż	A	B	CH1
50550 3-M5	19	24,5	9,0	3	M5	5	-
50550 4-M5	19	24,5	9,0	4	M5	5	-
50550 4-1/8	21	27	14,0	4	1/8	6	5
50550 5-M5	20	24,5	9,0	5	M5	5	-
50550 5-1/8	21,5	27	14,0	5	1/8	6	5
50550 5-1/4	24,5	31,0	18,0	5	1/4	8	6
50550 6-M5	20,5	24,5	9,0	6	M5	5	-
50550 6-1/8	22,5	27	14,0	6	1/8	6	5
50550 6-1/4	25	31,0	18,0	6	1/4	8	6
50550 8-1/8	24	27	14,0	8	1/8	6	5
50550 8-3/8	28	35,5	21,0	8	3/8	9	7
50550 8-1/4	26	31,0	18,0	8	1/4	8	6
50550 10-1/4	29	31,0	18,0	10	1/4	8	6
50550 10-3/8	30,5	35,5	21,0	10	3/8	9	7
50550 12-3/8	32,5	35,5	21,0	12	3/8	9	7