



## 50600 - Adapter connectors

Material:	Nickel-plated brass
Medium:	Compressed air, vacuum
Clamping ring:	Stainless steel AISI 304
Locking ring:	Technopolymer
Gasket:	NBR 70
Pressure:	max. 15 bar
Operating temperature:	-20°C To 80°C

Name	D	A	B	L	L1 (mm)	CH1
50600 4-M5	4	M5	5	25	15	8
50600 4-1/8	4	1/8	6	26,5	15	13
50600 5-M5	5	M5	5	27	17	8
50600 5-1/8	5	1/8	6	28,5	17	13
50600 5-1/4	5	1/4	8	31	17	16
50600 6-M5	6	M5	5	27	17	8
50600 6-1/8	6	1/8	6	28,5	17	13
50600 6-1/4	6	1/4	8	31	17	16
50600 8-1/8	8	1/8	6	29,5	18	13
50600 8-1/4	8	1/4	8	32	18	16
50600 8-3/8	8	3/8	9	33,5	18	20
50600 10-1/8	10,0	1/8	6	33,5	22	13
50600 10-1/4	10,0	1/4	8	36	22	16
50600 10-3/8	10,0	3/8	9	37,5	22	20
50600 12-1/4	12	1/4	8	38,5	24,5	16
50600 12-3/8	12	3/8	9	40	24,5	20