

Simple Plug nipple with external thread (O-ring)



medium:

compressed air, vacuum

body material:

plastic, nickel-plated brass

maximum pressure:

15 bar (vacuum)

Operating temperature:

0 to + 80 ° C

seal thread:

O-ring NBR

Application to conductors:

PU, PA, PE

Name	Screw	Waż	L1 (mm)	SW
122.005-4	M5	4	19,3	10
122.005-6	M5	6	20,7	12
122.018-4	G1/8	4	19,5	14
122.018-6	G1/8	6	20,4	14
122.018-8	G1/8	8	25,1	14
122.018-10	G1/8	10	28,3	17
122.018-12	G1/8	12	31,3	21
122.014-4	G1/4	4	18,1	17
122.014-6	G1/4	6	22,1	17
122.014-8	G1/4	8	23,5	17
122.014-10	G1/4	10	29,3	17
122.014-12	G1/4	12	32,6	21
122.038-6	G3/8	6	20,7	20
122.038-8	G3/8	8	21,1	20
122.038-10	G3/8	10	26,8	20
122.038-12	G3/8	12	29,6	21
122.038-16	G3/8	16	35,7	24
122.012-6	G1/2	6	24,7	24
122.012-8	G1/2	8	25,1	24
122.012-10	G1/2	10	25,1	24
122.012-12	G1/2	12	30,6	24
122.012-16	G1/2	16	37,5	24