



## Simple Plug nipple with external thread (Teflon)

medium:

compressed air, vacuum

body material:

plastic, nickel-plated b

maximum pressure:

15 bar (vacuum)

Operating temperature:

0 to + 80 ° C

seal thread:

O-ring NBR

Application to conductors:

PU, PA, PE

Name	Screw	L1 (mm)	SW	Waż
123.018-4	R1/8	19,8	10	10
123.018-6	R1/8	6	21	12
123.018-8	R1/8	8	25,9	14
123.018-10	R3/8	10	29,8	17
123.018-12	R3/8	12	31,6	21
123.014-4	R1/4	4	17,9	14
123.014-6	R1/4	6	22,7	14
123.014-8	R1/4	8	24,9	14
123.014-10	R1/4	10	30,8	17
123.014-12	R1/4	12	33,6	21
123.038-6	R3/8	6	20,7	17
123.038-8	R3/8	8	21,9	17
123.038-10	R3/8	10	28,3	17
123.038-12	R3/8	12	30,6	21
123.038-16	R3/8	16	38,1	24
123.012-6	R1/2	6	24,7	21
123.012-8	R1/2	8	25,9	21
123.012-10	R1/2	10	26,6	21
123.012-12	R1/2	12	33,6	21
123.012-16	R1/2	16	35,1	24