



AOS 90 - Swage nipple, DKOS angle 90°

Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1
Sealing form 1

metric nut thread
 24° outer cone with O-ring

Short code

DKOS

Standard

ISO 8434-1

Series

heavy

Material

Steel

Surface

electro galvanised

Name	DN	Size	Screw	φ
PN 04 AOS 90	4	3	M 16x1,5	8
PN 06 AOS 03 90	6	4	M 14x1,5	6
PN 06 AOS 04 90	6	4	M 16x1,5	8
PN 06 AOS 90	6	4	M 18x1,5	10
PN 06 AOS 08 90	6	4	M 20x1,5	12
PN 08 AOS 90	8	5	M 20x1,5	12
PN 08 AOS 06 90	8	5	M 18x1,5	10
PN 10 AOS 08 90	10	6	M 20x1,5	12
PN 10 AOS 90	10	6	M 22x1,5	14
PN 13 AOS 90	13	8	M 24x1,5	16
PN 13 AOS 16 90	13	8	M 30x2	20
PN 16 AOS 13 90	16	10	M 24x1,5	16
PN 16AOS 90	16	10	M 30x2	20
PN 20 AOS 16 90	20	12	M 30x2	20
PN 20 AOS 90	20	12	M 36x2	25
PN 25 AOS 20 90	25	16	M 36x2	25
PN 25 AOS 90	25	16	M 42x2	30
PN 32 AOS 25 90	32	20	M 42x2	30
PN 32 AOS 90	32	20	M 52x2	38