

Rotation Angle Plug nipple with external thread (O-ring)



| | |
|----------------------|------------------------------|
| medium: | compressed air vacuum |
| body material: | plastic, nickel-plated brass |
| maximum pressure: | 10 bar (vacuum) |
| working temperature: | -20 To + 60 ° C |
| seal thread: | O-ring or PTFE coating |

| Name | Screw | Waż | L1 (mm) | L2 (mm) | SW |
|------------|-------|-----|---------|---------|----|
| 125.005-4 | M5 | 4 | 17,5 | 17,0 | 10 |
| 125.005-6 | M5 | 6 | 19 | 17,5 | 12 |
| 125.018-4 | G1/8 | 4 | 17,7 | 24,5 | 14 |
| 125.018-6 | G1/8 | 6 | 19,3 | 25,7 | 14 |
| 125.018-8 | G1/8 | 8 | 22,8 | 29 | 14 |
| 125.014-4 | G1/4 | 4 | 17,7 | 27 | 17 |
| 125.014-6 | G1/4 | 6 | 19,3 | 28,2 | 17 |
| 125.014-8 | G1/4 | 8 | 22,8 | 31,5 | 17 |
| 125.014-10 | G1/4 | 10 | 27,6 | 35,8 | 17 |
| 125.014-12 | G1/4 | 12 | 29,6 | 38,0 | 21 |
| 125.038-6 | G3/8 | 6 | 19,3 | 29,7 | 20 |
| 125.038-8 | G3/8 | 8 | 22,8 | 33 | 20 |
| 125.038-10 | G3/8 | 10 | 27,6 | 37,3 | 20 |
| 125.038-12 | G3/8 | 12 | 29,6 | 39 | 21 |
| 125.038-16 | G3/8 | 16 | 33,0 | 40,5 | 24 |
| 125.012-6 | G1/2 | 6 | 19,3 | 33,7 | 24 |
| 125.012-8 | G1/2 | 8 | 22,8 | 37,0 | 24 |
| 125.012-10 | G1/2 | 10 | 27,6 | 41,3 | 24 |
| 125.012-12 | G1/2 | 12 | 29,6 | 43 | 24 |
| 125.012-14 | G1/2 | 14 | 31 | 43 | 24 |
| 125.012-16 | G1/2 | 16 | 32,5 | 43,5 | 24 |