



Rotation Angle Plug nipple with external thread (O-ring) long

medium:	compressed air vacuum
body material:	plastic, nickel-plated brass
maximum pressure:	10 bar (vacuum)
working temperature:	-20 To + 60 ° C
seal thread:	O-ring or PTFE coating

Name	Screw	Waż	L1 (mm)	L2 (mm)	SW
127.018-4	R1/8	4	17,5	36	10
127.018-6	R1/8	6	19	39,7	12
127.018-8	R1/8	8	22,8	44,8	14
127.018-10	R1/8	10	28	54,3	17
127.018-12	R1/8	12	30,0	61	21
127.014-4	R1/4	4	17,5	39	14
127.014-6	R1/4	6	19	42,2	14
127.014-8	R1/4	8	22,8	46,8	14
127.014-10	R1/4	10	28	56,3	17
127.014-12	R1/4	12	29,6	61,5	21
127.038-6	R3/8	6	19	43,7	17
127.038-8	R3/8	8	22,8	48,4	17
127.038-10	R3/8	10	28	57,3	17
127.038-12	R3/8	12	29,6	62,5	21
127.038-16	R3/8	13	33,0	72,5	24
127.012-6	R1/2	6	19	47,2	21
127.012-8	R1/2	8	22,8	51,8	21
127.012-10	R1/2	10	28	60,8	21
127.012-12	R1/2	12	29,6	65,5	21
127.012-16	R1/2	16	33,0	78,5	24
127.005-4	M5	4	-	-	-