



## Rotation Angle Plug nipple with external thread (O-ring) long

|                      |                              |
|----------------------|------------------------------|
| medium:              | compressed air vacuum        |
| body material:       | plastic, nickel-plated brass |
| maximum pressure:    | 10 bar (vacuum)              |
| working temperature: | -20 To + 60 ° C              |
| seal thread:         | O-ring or PTFE coating       |

| Name       | Screw | Waż | L1 (mm) | L2 (mm) | SW |
|------------|-------|-----|---------|---------|----|
| 127.018-4  | R1/8  | 4   | 17,5    | 36      | 10 |
| 127.018-6  | R1/8  | 6   | 19      | 39,7    | 12 |
| 127.018-8  | R1/8  | 8   | 22,8    | 44,8    | 14 |
| 127.018-10 | R1/8  | 10  | 28      | 54,3    | 17 |
| 127.018-12 | R1/8  | 12  | 30,0    | 61      | 21 |
| 127.014-4  | R1/4  | 4   | 17,5    | 39      | 14 |
| 127.014-6  | R1/4  | 6   | 19      | 42,2    | 14 |
| 127.014-8  | R1/4  | 8   | 22,8    | 46,8    | 14 |
| 127.014-10 | R1/4  | 10  | 28      | 56,3    | 17 |
| 127.014-12 | R1/4  | 12  | 29,6    | 61,5    | 21 |
| 127.038-6  | R3/8  | 6   | 19      | 43,7    | 17 |
| 127.038-8  | R3/8  | 8   | 22,8    | 48,4    | 17 |
| 127.038-10 | R3/8  | 10  | 28      | 57,3    | 17 |
| 127.038-12 | R3/8  | 12  | 29,6    | 62,5    | 21 |
| 127.038-16 | R3/8  | 13  | 33,0    | 72,5    | 24 |
| 127.012-6  | R1/2  | 6   | 19      | 47,2    | 21 |
| 127.012-8  | R1/2  | 8   | 22,8    | 51,8    | 21 |
| 127.012-10 | R1/2  | 10  | 28      | 60,8    | 21 |
| 127.012-12 | R1/2  | 12  | 29,6    | 65,5    | 21 |
| 127.012-16 | R1/2  | 16  | 33,0    | 78,5    | 24 |
| 127.005-4  | M5    | 4   | -       | -       | -  |