



Rotation Angle Plug nipple with external thread (Teflon) long

medium:	compressed air vacuum
body material:	plastic, nickel-plated brass
maximum pressure:	10 bar (vacuum)
working temperature:	-20 To + 60 ° C
seal thread:	O-ring or PTFE coating

Name	Screw	Waż	L1 (mm)	L2 (mm)	SW
128.018-4	G1/8	4	18,7	44,2	14
128.018-6	G1/8	6	19,6	45,6	14
128.018-8	G1/8	8	22,8	51,7	14
128.018-10	G1/8	10	28	54,3	17
128.018-12	G1/8	12	30,0	61	21
128.014-4	G1/4	4	18,7	46,7	17
128.014-6	G1/4	6	19,6	48,1	17
128.014-8	G1/4	8	22,8	54,2	17
128.014-10	G1/4	10	28,3	64,8	17
128.014-12	G1/4	12	29,6	67,6	21
128.038-6	G3/8	6	19,6	49,6	20
128.038-8	G3/8	8	22,8	55,7	20
128.038-10	G3/8	10	28,3	66,3	20
128.038-12	G3/8	12	29,6	68,6	21
128.038-16	G3/8	16	33,0	74	24
128.012-6	G1/2	6	19,6	53,6	24
128.012-8	G1/2	8	22,8	59,7	24
128.012-10	G1/2	10	28,3	70,3	24
128.012-12	G1/2	12	29,6	72,6	24
128.012-16	G1/2	16	33,0	78,5	24