



## Rotation Angle Plug nipple with internal thread conical

|                      |                              |
|----------------------|------------------------------|
| medium:              | compressed air vacuum        |
| body material:       | plastic, nickel-plated brass |
| maximum pressure:    | 10 bar (vacuum)              |
| working temperature: | -20 To + 60 ° C              |
| seal thread:         | O-ring or PTFE coating       |

| Name       | Screw  | Waż | L1 (mm) | L2 (mm) | SW |
|------------|--------|-----|---------|---------|----|
| 153.018-4  | Rc 1/8 | 4   | 18      | 23,0    | 14 |
| 153.018-6  | Rc 1/8 | 6   | 19      | 39      | 14 |
| 153.018-8  | Rc 1/8 | 8   | 23      | 27      | 14 |
| 153.014-6  | Rc 1/4 | 6   | 19      | 27      | 17 |
| 153.014-8  | Rc 1/4 | 8   | 23      | 30,0    | 17 |
| 153.014-10 | Rc 1/4 | 10  | 30,0    | 34      | 17 |
| 153.014-12 | Rc 1/4 | 12  | 30,0    | 37,0    | 21 |
| 153.038-8  | Rc 3/8 | 8   | 23      | 32,0    | 21 |
| 153.038-10 | Rc 3/8 | 10  | 30,0    | 36      | 21 |
| 153.038-12 | Rc 3/8 | 12  | 30,0    | 38,0    | 21 |
| 153.012-8  | Rc 1/2 | 8   | 23      | 34      | 24 |
| 153.012-10 | Rc 1/2 | 10  | 30,0    | 38,0    | 24 |
| 153.012-12 | Rc 1/2 | 12  | 30,0    | 41,0    | 24 |